



SIMATIC DP,BUS CONNECTOR FOR PROFIBUS UP TO 12 MBIT/S 90 DEGREE ANGLE CABLE OUTLET, IPCD TECHNOLOGY FAST CONNECT, WITHOUT PG SOCKET 15,8 X 59 X 35,6 MM (WXHXD),

Transfer rate

- with PROFIBUS

9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of electrical connections

- for PROFIBUS cables
- for network components and terminal equipment

2

1

Design of the electrical connection

- for network components and terminal equipment

9-pin Sub-D plug

Design of the electrical connection / FastConnect

Yes

Mechanical data

Material / of the enclosure

plastic

Design, dimensions and weight

Width

15.8 mm

Height

59 mm

Depth

35.6 mm

Net weight

10 g

Permitted ambient conditions

Ambient temperature

- during operating
- during storage
- during transport

0 ... 60 °C

-40 ... +70 °C

-40 ... +70 °C

Relative humidity	
• at 25 °C / without condensation / during operating / maximum	95 %
Protection class IP	IP20
Product properties, functions, components / general	
Product feature / [not supplied - silicon-free]	Yes
Product component	
• PG connection socket	No
• strain relief	Yes
Standards, specifications, approvals	
Verification of suitability	
• RoHS conformity	Yes
• UL-registration	Yes
letzte Änderung:	Oct 24, 2012