

## Data sheet

6GK1901-0DB20-6AA0

### Product type designation

Product description

### IE FC M12 Plug PRO (PROFINET)

M12 connector with high protection, 4-pole, D-coded  
Industrial Ethernet FastConnect M12 plug PRO 2x2 M12 plug-in  
connector with rugged metal enclosure and FC connection method,  
with axial cable outlet (D-coded) 1 pack=1 unit for SCALANCE X208  
PRO and ET 200 PRO PN



### Suitability for use

For connecting electrical cables to SCALANCE X208PRO, ET200  
PRO PN or ET200 eco PN for fast assembly with the FastConnect  
system

### Transfer rate

Transfer rate / for Industrial Ethernet

10 Mbit/s, 100 Mbit/s

### Interfaces

Number of electrical connections

- for Industrial Ethernet FC TP cables
- for network components or terminal equipment

4

1

Type of electrical connection

- for Industrial Ethernet FC TP cables
- for network components or terminal equipment

integrated cut-and-clamp contacts for 4-wire TP FC installation  
cable AWG22

M12 connector (D-coded)

Type of electrical connection / FastConnect

Yes

### Mechanical data

Material / of the enclosure

metal

Number of reuses

10

Locking mechanism design	Screw
Design, dimensions and weight	
Type of cable outlet	180° cable outlet
Width	19 mm
Height	19 mm
Depth	73 mm
Net weight	40 g
Ambient conditions	
Ambient temperature	
• during operation	-40 ... +85 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Chemical resistance	
• to water	resistant
Protection class IP	IP65/67
Product features, product functions, product components / general	
Product feature	
• PoE capability	Yes
• PoE+capability	Yes
• silicon-free	Yes
Product component	
• strain relief	Yes
Standards, specifications, approvals	
Certificate of suitability	
• RoHS conformity	Yes
• UL approval	Yes
• cULus approval	Yes
• Railway application in accordance with EN 50155	No
Standard for structured cabling	Cat5
Further information / Internet-Links	
Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	<a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a>
• to website: Industrial communication	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
• to website: Industry Mall	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
• to website: Information and Download Center	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
• to website: Image database	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>

- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

**last modified:**

12/14/2019