

SIMATIC S7-1200F, CPU 1214 FC, compact CPU, DC/DC/relay, onboard I/O: 14 DI 24 V DC; 10 DO relay 2 A; 2 AI 0-10 V DC, Power supply: DC 20.4-28.8V DC, Program/data memory 125 KB



### General information

|                          |                        |
|--------------------------|------------------------|
| Product type designation | CPU 1214FC DC/DC/Relay |
| Firmware version         | V4.2                   |
| Engineering with         |                        |
| • Programming package    | STEP 7 V14 or higher   |

### Supply voltage

|                                       |        |
|---------------------------------------|--------|
| Rated value (DC)                      |        |
| • 24 V DC                             | Yes    |
| permissible range, lower limit (DC)   | 20.4 V |
| permissible range, upper limit (DC)   | 28.8 V |
| Load voltage L+                       |        |
| • Rated value (DC)                    | 24 V   |
| • permissible range, lower limit (DC) | 20.4 V |
| • permissible range, upper limit (DC) | 28.8 V |

### Input current

|                           |   |
|---------------------------|---|
| Current consumption, max. | 1 500 mA; max. with all expansion accessories |
| Inrush current, max.      | 12 A; at 28.8 V DC                            |
| I <sub>2t</sub>           | 0.5 A <sup>2</sup> ·s                         |

|   |  |   |
|---|--|---|
| Output current  |  |   |
| for backplane bus (5 V DC), max.                          |  | 1 600 mA; Max. 5 V DC for SM and CM   |
| Encoder supply  |  |   |
| 24 V encoder supply                                       |  |   |
| • 24 V  |  | L+ minus 4 V DC min.  |
| Power loss  |  |   |
| Power loss, typ.  |  | 12 W  |
| Memory  |  |   |
| Work memory   |  |   |
| • integrated  |  | 125 kbyte   |
| • expandable  |  | No  |
| Load memory   |  |   |
| • integrated  |  | 4 Mbyte   |
| • Plug-in (SIMATIC Memory Card), max.                     |  | with SIMATIC memory card  |
| Backup  |  |   |
| • present   |  | Yes   |
| • maintenance-free  |  | Yes   |
| • without battery   |  | Yes   |
| CPU processing times                                      |  |   |
| for bit operations, typ.                                  |  | 0.08 µs; / instruction  |
| for word operations, typ.                                 |  | 1.7 µs; / instruction   |
| for floating point arithmetic, typ.                       |  | 2.3 µs; / instruction   |
| CPU-blocks  |  |   |
| Number of blocks (total)                                  |  | DBs, FCs, FBs, counters and timers. The maximum number of addressable blocks ranges from 1 to 65535. There is no restriction, the entire working memory can be used |
| OB  |  |   |
| • Number, max.  |  | Limited only by RAM for code  |
| Data areas and their retentivity                          |  |   |
| Retentive data area (incl. timers, counters, flags), max. |  | 10 kbyte  |
| Flag  |  |   |
| • Number, max.  |  | 8 kbyte; Size of bit memory address area  |
| Address area  |  |   |
| Process image   |  |   |
| • Inputs, adjustable                                      |  | 1 kbyte   |
| • Outputs, adjustable                                     |  | 1 kbyte   |
| Hardware configuration                                    |  |   |
| Number of modules per system, max.                        |  | 3 comm. modules, 1 signal board, 8 signal modules   |

|   |   |
|---|---|
| <b>Time of day</b>                                    |   |
| <b>Clock</b>  |   |
| • Hardware clock (real-time)                          | Yes   |
| • Backup time   | 480 h; typical; 12 days min. at 40 °C   |
| • Deviation per day, max.                             | ±60 s per month   |
| <b>Digital inputs</b>                                 |   |
| Number of digital inputs                              | 14  |
| • of which inputs usable for technological functions  | 6; HSC (High Speed Counting)  |
| Source/sink input                                     | Yes   |
| <b>Number of simultaneously controllable inputs</b>   |   |
| all mounting positions                                |   |
| — up to 40 °C, max.                                   | 14; 14 inputs at 55 °C horizontal or 45 °C vertical   |
| <b>Input voltage</b>                                  |   |
| • Rated value (DC)                                    | 24 V; DC at 4 mA nominal  |
| • for signal "0"                                      | 5 V DC at 1 mA  |
| • for signal "1"                                      | 15 V DC at 2.5 mA   |
| <b>Input current</b>                                  |   |
| • for signal "1", typ.                                | 4 mA; nominal   |
| <b>Input delay (for rated value of input voltage)</b> |   |
| for standard inputs                                   |   |
| — parameterizable                                     | 0.1 / 0.2 / 0.4 / 0.8 / 1.6 / 3.2 / 6.4 / 10.0 / 12.8 / 20.0 µs; 0.05 / 0.1 / 0.2 / 0.4 / 0.8 / 1.6 / 3.2 / 6.4 / 10.0 / 12.8 / 20.0 ms |
| — at "0" to "1", min.                                 | 0.1 µs  |
| — at "0" to "1", max.                                 | 20 ms   |
| for interrupt inputs                                  |   |
| — parameterizable                                     | Yes   |
| for technological functions                           |   |
| — parameterizable                                     | Yes; Single phase: 3 @ 100 kHz & 3 @ 30 kHz, differential: 3 @ 80 kHz & 3 @ 30 kHz  |
| <b>Cable length</b>                                   |   |
| • shielded, max.                                      | 500 m; 50 m for technological functions   |
| • unshielded, max.                                    | 150 m; for technological functions: No  |
| <b>Digital outputs</b>                                |   |
| Number of digital outputs                             | 10  |
| <b>Relay outputs</b>                                  |   |
| • Number of relay outputs                             | 10  |
| <b>Analog inputs</b>                                  |   |
| Number of analog inputs                               | 2   |
| <b>Input ranges</b>                                   |   |
| • Voltage   | Yes   |

|  |                             |
|--|-----------------------------|
| Input ranges (rated values), voltages                  |                             |
| • 0 to +10 V   | Yes                         |
| • Input resistance (0 to 10 V)                         | ≥100k ohms                  |
| Cable length   |                             |
| • shielded, max.                                       | 100 m; twisted and shielded |
| Analog outputs   |                             |
| Number of analog outputs                               | 0                           |
| Output ranges, current                                 |                             |
| • 0 to 20 mA   | Yes                         |
| Analog value generation for the inputs                 |                             |
| Integration and conversion time/resolution per channel |                             |
| • Resolution with overrange (bit including sign), max. | 10 bit                      |
| • Integration time, parameterizable                    | Yes                         |
| • Conversion time (per channel)                        | 625 μs                      |
| Encoder  |                             |
| Connectable encoders                                   |                             |
| • 2-wire sensor  | Yes                         |
| 1. Interface   |                             |
| Interface type   | PROFINET                    |
| Physics  | Ethernet                    |
| Isolated   | Yes                         |
| automatic detection of transmission rate               | Yes                         |
| Autonegotiation  | Yes                         |
| Autocrossing   | Yes                         |
| Interface types  |                             |
| • Number of ports                                      | 1                           |
| • integrated switch                                    | No                          |
| Protocols  |                             |
| • PROFINET IO Controller                               | Yes                         |
| • PROFINET IO Device                                   | Yes                         |
| • SIMATIC communication                                | Yes                         |
| • Open IE communication                                | Yes                         |
| • Web server   | Yes                         |
| • Media redundancy                                     | No                          |
| PROFINET IO Controller                                 |                             |
| • Transmission rate, max.                              | 100 Mbit/s                  |
| Services   |                             |
| — PG/OP communication                                  | Yes                         |
| — S7 routing   | Yes                         |
| — Isochronous mode                                     | No                          |

|   |   |
|---|---|
| — Open IE communication   | Yes   |
| — IRT   | No  |
| — MRP   | No  |
| — MRPD  | No  |
| — PROFlenergy   | No  |
| — Prioritized startup   | Yes   |
| — Number of IO devices with prioritized startup, max.                         | 16  |
| — Number of connectable IO Devices, max.                                      | 16  |
| — Number of connectable IO Devices for RT, max.                               | 16  |
| — of which in line, max.  | 16  |
| — Activation/deactivation of IO Devices                                       | Yes   |
| — Number of IO Devices that can be simultaneously activated/deactivated, max. | 8   |
| — Updating time   | The minimum value of the update time also depends on the communication component set for PROFINET IO, on the number of IO devices and the quantity of configured user data. |

#### PROFINET IO Device

##### Services

|   |     |
|---|-----|
| — PG/OP communication                               | Yes |
| — S7 routing  | Yes |
| — Isochronous mode                                  | No  |
| — Open IE communication                             | Yes |
| — IRT   | No  |
| — MRP   | No  |
| — MRPD  | No  |
| — PROFlenergy                                       | Yes |
| — Shared device                                     | Yes |
| — Number of IO Controllers with shared device, max. | 2   |

#### Protocols

|                                   |   |
|-----------------------------------|---|
| Supports protocol for PROFINET IO | Yes   |
| PROFIBUS                          | Yes; CM 1243-5 (master) or CM 1242-5 (slave) required |
| AS-Interface                      | Yes; CM 1243-2 required                               |

##### Protocols (Ethernet)

|          |     |
|----------|-----|
| • TCP/IP | Yes |
| • DHCP   | No  |
| • SNMP   | Yes |
| • DCP    | Yes |
| • LLDP   | Yes |

##### Open IE communication

|  |  |
|--|--|
| • TCP/IP   | Yes  |
| — Data length, max.                                      | 8 kbyte  |
| • ISO-on-TCP (RFC1006)                                   | Yes  |
| — Data length, max.                                      | 8 kbyte  |
| • UDP  | Yes  |
| — Data length, max.                                      | 1 472 byte   |
| <b>Web server</b>  |  |
| • supported  | Yes  |
| • User-defined websites                                  | Yes  |
| <b>Further protocols</b>                                 |  |
| • MODBUS   | Yes  |
| <b>Communication functions</b>                           |  |
| <b>S7 communication</b>                                  |  |
| • supported  | Yes  |
| • as server  | Yes  |
| • as client  | Yes  |
| • User data per job, max.                                | See online help (S7 communication, user data size)                   |
| <b>Number of connections</b>                             |  |
| • overall  | 16; dynamically  |
| <b>Test commissioning functions</b>                      |  |
| <b>Status/control</b>                                    |  |
| • Status/control variable                                | Yes  |
| • Variables  | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters |
| <b>Forcing</b>   |  |
| • Forcing  | Yes  |
| <b>Diagnostic buffer</b>                                 |  |
| • present  | Yes  |
| <b>Traces</b>  |  |
| • Number of configurable Traces                          | 2  |
| • Memory size per trace, max.                            | 512 kbyte  |
| <b>Integrated Functions</b>                              |  |
| Number of counters                                       | 6  |
| Counting frequency (counter) max.                        | 100 kHz  |
| Frequency measurement                                    | Yes  |
| controlled positioning                                   | Yes  |
| Number of position-controlled positioning axes, max.     | 8  |
| Number of positioning axes via pulse-direction interface | Up to 4 with SB 1222   |
| PID controller   | Yes  |
| Number of alarm inputs                                   | 4  |

## EMC

### Interference immunity against conducted variable disturbance induced by high-frequency fields

- Interference immunity against high-frequency radiation acc. to IEC 61000-4-6

Yes

### Emission of radio interference acc. to EN 55 011

- Limit class A, for use in industrial areas
- Limit class B, for use in residential areas

Yes; Group 1

Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011

## Standards, approvals, certificates

### CE mark

Yes

### UL approval

Yes

### cULus

Yes

### FM approval

Yes

### RCM (formerly C-TICK)

Yes

### KC approval

Yes

### Marine approval

Yes

### Highest safety class achievable in safety mode

- Performance level according to ISO 13849-1
- SIL acc. to IEC 61508

PLe

SIL 3

## Ambient conditions

### Ambient temperature during operation

- min. 0 °C
- max. 55 °C
- horizontal installation, min. 0 °C
- horizontal installation, max. 55 °C
- vertical installation, min. 0 °C
- vertical installation, max. 45 °C

### Ambient temperature during storage/transportation

- min. -40 °C
- max. 70 °C

### Air pressure acc. to IEC 60068-2-13

- Storage/transport, min. 660 hPa
- Storage/transport, max. 1 139 hPa

### Relative humidity

- Operation, max. 95 %; no condensation

### Vibrations

- Vibration resistance during operation acc. to IEC 60068-2-6 2 g (m/s<sup>2</sup>) wall mounting, 1 g (m/s<sup>2</sup>) DIN rail
- Operation, tested according to IEC 60068-2-6 Yes

### Shock testing

- tested according to IEC 60068-2-27 Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms

|   |  |
|---|--|
| Pollutant concentrations                      |  |
| • SO2 at RH < 60% without condensation        | SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free |
| Configuration                                 |  |
| Programming                                   |  |
| Programming language                          |  |
| — LAD   | Yes; incl. failsafe  |
| — FBD   | Yes; incl. failsafe  |
| — SCL   | Yes  |
| Know-how protection                           |  |
| • User program protection/password protection | Yes  |
| • Copy protection                             | Yes  |
| • Block protection                            | Yes  |
| Cycle time monitoring                         |  |
| • adjustable                                  | Yes  |
| Dimensions                                    |  |
| Width   | 110 mm   |
| Height  | 100 mm   |
| Depth   | 75 mm  |
| Weights                                       |  |
| Weight, approx.                               | 435 g  |
| <b>last modified:</b>                         | 12/14/2019   |