SIEMENS

Data sheet

6GK1900-1RB00-2AB0

Product type designation Product description

FC FO LC Plug

LC-Duplex connector for FastConnect mounting FC FO LC plug for on-site mounting to FC FOC cables (62.5/200/230) Pack: 10 units duplex plugs +cleaning cloths



Suitability for use	For connecting glass fiber-optic cables, suitable for fast assembly with the FastConnect FO system
Transfer rate	
Transfer rate / for Industrial Ethernet	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s
Interfaces	
Type of electrical connection	
• for PROFIBUS cables	RJ45 connector (Push Pull device connection)
Number of optical interfaces / for fiber optic cable	1
Type of electrical connection / FastConnect	Yes
Mechanical data	
Material / of the enclosure	plastic
Number of reuses	1
Design, dimensions and weight	
Type of cable outlet	180° cable outlet
Ambient conditions	
Ambient temperature	

during operation	-40 +85 °C
during storage	-40 +85 °C
during transport	-40 +85 °C
Chemical resistance	
• to water	resistant
Protection class IP	IP20

Product features, product functions, product components / general		
Product feature		
 PoE capability 	No	
PoE+capability	No	
• silicon-free	Yes	
Product component		
• strain relief	Yes	

Standards, specifications, approvals Certificate of suitability • RoHS conformity

RoHS conformity
 UL approval
 cULus approval
 Railway application in accordance with EN

Further information / Internet-Links

Internet-Link

50155

• to website: Selector SIMATIC NET

SELECTION TOOL

http://www.siemens.com/snst

to website: Industrial communication
 to website: Industry Mall
 https://mall.industry.siemens.com

to website: Information and Download Center
 to website: Image database
 to website: CAx Download Manager
 http://www.siemens.com/industry/infocenter
 http://www.siemens.com/bilddb
 http://www.siemens.com/cax

• to website: Industry Online Support

https://support.industry.siemens.com

last modified: 12/14/2019