

Gegevensblad product

Kenmerken

LV429407

Minimumspanningsuitschakelspoel MN 208-277V/220-240VWS Compact NSX



Hoofdkenmerken

Gamma	ComPacT
Productgamma	ComPacT NSX100...250 ComPacT NSX100...250 new generation ComPacT NSX400...630 ComPacT NSX400...630 new generation ComPacT NSX100...250 DC ComPacT NSX100...250 DC new generation ComPacT NSX100...250 DC PV ComPacT NSX100...250 DC PV new generation ComPacT NSX400...630 DC ComPacT NSX400...630 DC new generation ComPacT NSX400...630 DC PV ComPacT NSX400...630 DC PV new generation
Korte naam apparaat	MN
Type product of component	Spanningsuitschakeling
Apparaattoepassing	Besturing
Type spanningsuitschakeling	Starter Minimumspanningsuitschakelspoel
[Uc] spanning stuurkring	220...240 V AC 50/60 Hz 208...277 V AC 60 Hz
Bereik compatibiliteit	ComPacT new generation (ComPacT NSX new generation) ComPacT new generation (ComPacT NSX DC new generation) Compact (Compact NSX) Compact (ComPacT NSX DC) Easypact (EasyPact CVS) PowerPact (PowerPact Multistandard)

Complementaire kenmerken

Operating threshold	0,35...0,7 x Un openen 0,85 x Un sluiten
Responstijd	50 ms
Houdvermogen voeding	5 VA
Inschakelvermogen voeding	10 VA
Aansluitklemmen	Spring 0,5...1,5 mm ² (AWG 20...AWG 16)
Draadstriplengte	7 mm

Verpakkingseenheden

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4,5 cm
Package 1 Width	4,6 cm
Package 1 Length	6,0 cm
Package 1 Weight	120,0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	7,2 cm
Package 2 Width	10,4 cm

Package 2 Length	23,5 cm
Package 2 Weight	1,252 kg
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Height	30,0 cm
Package 3 Width	30,0 cm
Package 3 Length	40,0 cm
Package 3 Weight	7,896 kg

Duurzaamheid van het aanbod

Status handhaafbaar aanbod	Green Premium-product
REACH-regelgeving	 REACH-verklaring
EU-richtlijn RoHS	Conform  EU-verklaring RoHS
Kwikvrij	Ja
RoHS-regulering China	 RoHS-verklaring China
Informatie over RoHS-vrijstelling	 Ja
Milieu-informatie	 Milieuprofiel Van Het Product
WEEE	Het product moet op markten van de Europese Unie worden afgevoerd volgens specifieke afvalinzamelingsregels en mag nooit in een gewone vuilnisbak terechtkomen.
PVC-vrij	Ja

Contractuele waarborg

Garantie	18 months
----------	-----------