

Gegevensblad product

Kenmerken

LV429516

1 korte klemmenafdekkap 4p voor Compact NSX100-250F/N/H/S/L-INS/INV100-250



Hoofdkenmerken

Type product of component	Korte klemmenafdekklep
Bereik compatibiliteit	ComPacT new generation (ComPacT NSX100 new generation) ComPacT new generation (ComPacT NSX160 new generation) ComPacT new generation (ComPacT NSX250 new generation) Compact (ComPacT NSX100) Compact (ComPacT NSX160) Compact (ComPacT NSX250) ComPacT new generation (ComPacT NSX DC new generation) NSX100 DC ComPacT new generation (ComPacT NSX DC new generation) NSX160 DC ComPacT new generation (ComPacT NSX DC new generation) NSX250 DC Compact Compact NSX100 DC Compact Compact NSX160 DC Compact Compact NSX250 DC Easypact (EasyPact CVS100) Easypact (EasyPact CVS160) Easypact (EasyPact CVS250)
Type toebehoren/aparte onderdelen	Isolatie toebehoren
Beschrijving polen	4P
Hoeveelheid per set	1

Complementaire kenmerken

Hartafstand aansluiting	35 mm
IP-beschermingsgraad	IP40 conform IEC 60529
Compatibiliteit product	Stroomonderbreker Plug-in basis

Verpakkingseenheden

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3,5 cm
Package 1 Width	15,8 cm
Package 1 Length	16,5 cm
Package 1 Weight	73,5 g
Unit Type of Package 2	S04
Number of Units in Package 2	40
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	3,726 kg
Unit Type of Package 3	P12
Number of Units in Package 3	160
Package 3 Height	50 cm

Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	26,904 kg

Duurzaamheid van het aanbod

Status handhaafbaar aanbod	Green Premium-product
REACH-regelgeving	REACH-verklaring
REACH vrij van SVHC	Ja
EU-richtlijn RoHS	Pro-actieve naleving (product valt buiten juridisch toepassingsgebied RoHS EU) EU-verklaring RoHS
Vrij van giftige zware metalen	Ja
Kwikvrij	Ja
RoHS-regulering China	RoHS-verklaring China
Informatie over RoHS-vrijstelling	Ja
Milieu-informatie	Milieuprofiel Van Het Product

Contractuele waarborg

Garantie	18 months
----------	-----------