

Gegevensblad product Kenmerken

AP4421

RACK ATS, 230V, 10A, C14 IN, (12) C13 OUT



Overzicht

Presentatie

The APC Rack Automatic Transfer Switch (ATS) is a high availability switch that provides redundant power to connected equipment and has two input power cords, one for each AC source. The output configuration is (12) IEC 60320 C13 The Rack ATS supplies power to the connected load from a primary AC source. If that primary source becomes unavailable, the Rack ATS automatically transfers loads to the secondary source. The transfer time from one source to the other is seamless to the connected equipment, as the switching occurs safely between the two input sources regardless of any phase differences. The units have built-in network connectivity, which allows for remote management through Web, SNMP, SSH, Telnet, or StruxureWare™ Data Center Expert. With multiple outlets, several devices can be plugged directly into the Rack ATS without the need for an additional Rack PDU. Current monitoring and alarms help prevent downtime to the equipment by providing aggregate current measurements and warnings when power consumption draws near the maximum rating of the Rack ATS. Built-in network and local interfaces allow for custom configuration settings for added flexibility.

Levertijd

Meestal op voorraad

Hoofdkenmerken

Main Input Voltage	230 V
Main Output Voltage	230 V
Input Connection Type	IEC 60320 C14
Aantal rekeenheden	1U
Meegeleverde apparatuur	Bevestigingshardware Rek inbouwbeugels Seriele configuratiekabel

Fysisch

Kleur	Zwart
Hoogte	4,4 cm
Breedte	43,2 cm
Diepte	23,6 cm
Gewicht product	3,93 kg
Montagelocatie	Voorzijde Achterkant
Mounting preference	No preference
Montagemodus	Gemonteerd op rack

Ingang

Netfrequentie	50/60 Hz
Max line current	10 A
Beperkingen inputstroom	10 A
Belastingcapaciteit	2000 VA

Uitgang

Max. totale stroomopname per fase	10 A
Number of power socket outlets	12 IEC 60320 C13
Type beveiliging	Without circuit breaker

Conformiteit

Normen	EN 55022 class A FCC deel 15 klasse A
--------	--

Milieu

Omgevingstemperatuur bij werking	-5...45 °C
Relatieve vochtigheid	5...95 %
Werkingshoogte	0...10000 ft
Omgevingstemperatuur bij opslag	-25...65 °C
Relatieve luchtvochtigheid voor opslag	5...95 %
Opslaghoogte	0,00...15240,00 m

Verpakkingseenheden

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11,500 cm
Package 1 Width	36,000 cm
Package 1 Length	60,000 cm
Package 1 Weight	5,535 kg
Unit Type of Package 2	P12
Number of Units in Package 2	8
Package 2 Height	45,000 cm
Package 2 Width	80,000 cm
Package 2 Length	120,000 cm
Package 2 Weight	56,288 kg

Duurzaamheid van het aanbod

Status handhaafbaar aanbod	Green Premium-product
REACH-regelgeving	 REACH-verklaring
EU-richtlijn RoHS	Conform  EU-verklaring RoHS
Loodvrij	Ja
Kwikvrij	Ja
Informatie over RoHS-vrijstelling	 Ja
Milieu-informatie	 Milieuprofiel Van Het Product
Circulariteitsprofiel	 Informatie Over Einde Levensduur
Take-back	Take-back program available

Contractuele waarborg

Garantie	2 jaar repareren of vervangen
----------	-------------------------------