ERSADUR longlife soldering tip series **832, 842** and **852**

Lead-free
Bleifrei
SAFE ersa

- ANALOG 60/60 A
- ANALOG 80/80 A
- DIGITAL 80 A
- DIGITAL 2000 A with POWER TOOL soldering iron
- ELS 8000/M/D
- Ersa 15+ / 25+ / 35+
- MICRO-CON 60 iA with POWER TOOL soldering iron
- MS 6000 / MS 8000/D
- MULTI-PRO
- MULTI-SPRINT
- MULTI-TC
- RDS 80
- TWIN 80 A with ERGO TOOL

0832UD/UDLF



pencil point, 0.4 mm ø, extended

0832SD/SDLF



pencil point, 0,8 mm ø, extended

0832BD/BDLF



pencil point, 1.0 mm ø

0832YD/YDLF



chisel-shaped, 1.6 mm

0832CD/CDLF



chisel-shaped, 2.2 mm

0832KD/KDLF



chisel-shaped, 2.2 mm, extended

0832ED/EDLF



chisel-shaped, 3,2 mm

0832VD/VDLF



chisel-shaped, 5.0 mm

0832FDLF



angled face, 2.0 mm

0832TDLF



angled face, 3.0 mm ø

0832NDLF



angled face, 4.0 mm ø

0832PW



PowerWell with concave portion

0832HD



SolderWell with concave portion, bent

0832AD



PLCC blade, 1.5 mm

08520D



PLCC blade, 2.0 mm

0832WD



chisel-shaped, 2.5 mm, bent

0832RD



chisel-shaped, 5.0 mm, bent

0832GDLF



angled face, 14 mm, 35°

0832LDLF



angled face, 17 mm, 35°

0832MDLF



angled face on both sides, 8 mm

0842UD/UDLF



pencil point, 0.4 mm ø, extended

0842SD/SDLF



pencil point, 0.8 mm ø, extended

0842BD/BDLF



pencil point, 1.0 mm ø

0842YD/YDLF



chisel-shaped, 1,6 mm

0842CD/CDLF



chisel-shaped, 2.2 mm

0842KD/KDLF



chisel-shaped, 2,2 mm, extended

0842ED/EDLF



chisel-shaped, 3.2 mm

0842ID



pencil point, 0.4 mm ø, bent

0842JD



chisel-shaped, 2.2 mm, bent

0852GD



angled face, 8.0 mm

0852VD



chisel-shaped, 5.0 mm

Dimensions without pre-tinning