



BE LGN20 HF FIRE-SNA 3x1,5 H3

Preflex SAFE 20mm+Pyro SNA (LS0H) 3X1.5 H300

Properties of the article

◦ Articlenumber	1234000040
◦ Barcode	5420056245272
◦ Category	Fire
◦ Gross weight (kg)	52.5
◦ Dimensions (WxLxH)	500 x 500 x 200 MM
◦ Packaging	Reel Ø 80 cm
◦ Length	300

Properties of the Preflex® tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Light Green
◦ Outer diameter (mm)	20
◦ Inner diameter (mm)	14.1
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

Characteristics of the cable or cable combination

	FIRE SNA 3x1.5
◦ Cable type	
◦ Color	
◦ Insulation	
◦ CPR Class	

Certificates

- Norm van de buis
- Norm van de kabel

Certificates

