



BE GY25 LF TD R0,25

Preflex 25mm+with pull wire+Low-Friction C 25

Properties of the article

◦ Articlenumber	1234000264
◦ Barcode	5420056214520
◦ Category	Empty
◦ Gross weight (kg)	3.7
◦ Dimensions (WxLxH)	500 x 500 x 200 MM
◦ Packaging	Roll
◦ Length	25

Properties of the Preflex® tube

◦ Material of tube	Polypropylene with Low-Frcition layer
◦ Color	Grey
◦ Outer diameter (mm)	25
◦ Inner diameter (mm)	18.3
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

Characteristics of the cable or cable combination

◦ Cable type	Trekdraad
◦ Color	
◦ Insulation	
◦ CPR Class	

Certificates

◦ Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1,
◦ Norm van de kabel	EN 60754-2

Certificates

