


MINI 6

- Ronde mini-grondspot.
- LED wit (3000K, 6000K) of blauw (BL).
- Kabel van 1.50m meegeleverd.
- Omvormer 12Vdc afzonderlijk te bestellen.



CODE	MATERIAAL	DC	LED	T° (K)	Nominal Lumen	System Lumen
KO91WW	ALUMINIUM	DC 12V	0,12W	3000K	15 Lm	6 Lm
KO91CL	ALUMINIUM	DC 12V	0,12W	6000K	15 Lm	6 Lm
KO91BL	ALUMINIUM	DC 12V	0,12W	BL	-	-

VOEDING	Watt Max	PRI	SEC	INPUTS	OUTPUTS	Max Case T°	Max Amb. T°
KAW16W	20W	AC 230V	DC 12V	2	1	80°C	50°C



Alleen op de grond in inbouw monteren.



Inbouw Wandmontage alleen.



Buitengebruik.



Stofdicht. Bescherming tegen waterstralen.



Weerstand : 0,23 Joule.



Product aangedreven door een laag voltage (SELV) die niet groter is dan 50V (AC RMS).



Gatdiameter voor de armatuur in te voegen. (14 mm)



Lichtbundel 90°.



CE gekeurd.



CRI>80



LED-specificaties.



RG1.



Getest bij 650°.



Voeding afzonderlijk te bestellen.



Parellele schakeling.



Aan te sluiten op een constante spanning Led voeding van 12VDC.



3 jaar garantie.