

ATS626

16-way output expander, plug-in, Advisor Advanced

Specifications

Supply voltage	10.5-13.8 (supplied through control panel)
Current consumption	50 mA (standby)
Open collector current (max)	
Low current	50 mA
High current	1A
Operating temperature	0 to +50°C
Humidity	95% non condensing
Dimensions (h x w x d)	40 x 90 x 18mm

Ordering Information

Part No.	Description
ATS626	16-way output expander, plug-in, Advisor Advanced
ATS1000A-SM	Advisor Advanced ATS1000A control panel in small metal housing, EN grade 2, 8 - 32 zones, 4 areas, 1A PSU, multi-lingual. Wired or wireless (hybrid) using plug-in or remote DGP's. Max 8 keypads/readers and 7 DGP's. Different housings available
ATS1000A-MM	Advisor Advanced ATS1000A control panel in medium metal housing, EN grade 2, 8 - 32 zones, 4 areas, 1A PSU, multilingual. Wired or wireless (hybrid) using plug-in or remote DGP's. Max 8 keypads/readers and 7 DGP's. Different housings available
ATS2000A-MM	Advisor Advanced ATS2000A control panel in medium metal housing, EN grade 2, 8 - 64 zones, 8 areas, 2A PSU, multilingual. Wired or wireless (hybrid) using plug-in or remote DGP's. Max 8 keypads/readers and 7 DGP's. Different housings available
ATS608	8-way input expander, plug-in, Advisor Advanced
ATS1631	ATS Output connector lead
ATS1810	ATS 4-way relay card

