

# ATS1500A-IP-MM-HK Kit ATS1500A-IP-MM including ATS1135 keypad



## **Details**

- 8 onboard zone inputs
- Max 32 zones: wired, wireless or mixed
- Economic input and output plug-in expansion
- Up to 16 shock sensor inputs
- 4 areas
- Up to 50 users
- EN50131 Grade 3 (when ATS-MM-TK added) / Environmental class 2
- USB port for local configuration
- Plug-on PSTN dialler for reporting or configuration
- Multilingual: language configurable per user
- Integrated 10/100Mb Ethernet connection
- IP alarm reporting to OH-NETREC receiver Optional GPRS
- Integrated access control & support for ATS125x door controller

## ATS1500A-IP-MM-HK Kit ATS1500A-IP-MM including ATS1135 keypad

## **Technical specifications**

System	
Product type	Integrated Access Control
Panel type	Hybrid
No. of keypads / readers	,
Data Gathering Panels	15
(DGP)	
No. of alarm groups	16
Specified cable	WCAT52, WCAT54
Inputs	
Max no. of inputs	32
Onboard inputs	8
Inputs plug-in expansion	8
Outputs	
No. of outputs	128
No. of onboard outputs	5
Area	
No. of areas	4
	•
User/Cards	
Max. no. of users	50
Max. no. of cards	50
Max. no. of PIN codes	50
Access control	
Standard doors on	4
control panel	120
Door groups	128
Intelligent doors on 4-door DGPs	28
Communication	
Onboard transmission	IP
type Transmission extension	GSM/GPRS, PSTN
Databus type	RS485
Evention	
Event log	10000
	10000
Electrical	
Power supply type	230 VAC
Power supply value	230 VAC +10%, -15%, 50 Hz
Mainboard current consumption	150 mA
Max system current	950 mA at 13.8 V ±0.2 V
Max aux power current	840 mA
Auto-reset fuses	5
Glass break fuses	1
	-
Physical	
Physical dimensions	315 × 388 × 85 mm
Housing	Medium Metal

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

### Environmental

Operating temperature	-10 to +55°C
Relative humidity	95% (non-condensing)
Environmental Class	Class II, indoor
IP rating	30

#### Standards & regulation

EN50131 Grade	Grade 3
Compliancy	CE

