

Number of contacts

6 +



Inserts

Han
E/EE

		Part No.																							
Identification	Series	Male insert (M)	Female insert (F)	Drawing	Dimensions in mm																				
Screw terminal with wire protection	Han E®	09 33 006 2601	09 33 006 2701	1) Distance for contact max. 21 mm <table border="1"><thead><tr><th></th><th>a</th><th>b</th><th>c</th><th>d</th></tr></thead><tbody><tr><td>Han E® screw</td><td>18</td><td>33</td><td>18</td><td>35</td></tr><tr><td>Han® ES/Han E® crimp</td><td>19</td><td>34</td><td>19</td><td>36</td></tr><tr><td>Han ESS</td><td>34</td><td>49</td><td>32</td><td>49</td></tr></tbody></table>			a	b	c	d	Han E® screw	18	33	18	35	Han® ES/Han E® crimp	19	34	19	36	Han ESS	34	49	32	49
	a	b	c	d																					
Han E® screw	18	33	18	35																					
Han® ES/Han E® crimp	19	34	19	36																					
Han ESS	34	49	32	49																					
Cage-clamp terminal	Han® ES	09 33 006 2616	09 33 006 2716																						
Cage-clamp terminal two terminals per contact	Han® ESS	09 33 006 2672	09 33 006 2772																						
Crimp terminal Order contacts separately	Han E®	09 33 006 2602	09 33 006 2702	Contact arrangement View from termination side Panel cut out for inserts for use without hoods/housings																					

Wire gauge		Part No.		Drawing	Dimensions in mm
Identification	(mm²)	Male contacts	Female contacts		
Crimp contacts					
Power contacts					
silver plated	0.14-0.37	09 33 000 6127*	09 33 000 6227*		
	0.5	09 33 000 6121	09 33 000 6220		
	0.75	09 33 000 6114	09 33 000 6214		
	1.0	09 33 000 6105	09 33 000 6205		
	1.5	09 33 000 6104	09 33 000 6204		
	2.5	09 33 000 6102	09 33 000 6202		
	3	09 33 000 6106	09 33 000 6206		
	4	09 33 000 6107	09 33 000 6207		
gold plated	0.14-0.37	09 33 000 6117*	09 33 000 6217*		
	0.5	09 33 000 6122	09 33 000 6222		
	0.75	09 33 000 6115	09 33 000 6215		
	1.0	09 33 000 6118	09 33 000 6218		
	1.5	09 33 000 6116	09 33 000 6216		
	2.5	09 33 000 6123	09 33 000 6223		
	4.0	09 33 000 6119	09 33 000 6221		
	Relay contact silver plated	0.75-1	09 33 000 6109		
1.5		09 33 000 6110			
2.5		09 33 000 6111			
Coding Pin		09 33 000 9954		Use of the coding pin prevents incorrect mating to other connectors of the same type. The male pin should be omitted from the opposing cavity in the male insert.	

* only to be used with BUCHANAN crimping tool 09 99 000 0001 and adjustment gauge 09 99 000 0203

Stock items in bold type