

Number of contacts



10 +


Inserts



Identification	Series	Part No.		Drawing	Dimensions in mm
		Male insert (M)	Female insert (F)		
Screw terminal 	Han A®	09 20 010 2612	09 20 010 2812		Screw terminal
Crimp terminal Order crimp contacts separately 	Han A®	09 20 010 3001	09 20 010 3101		Crimp terminal

¹⁾ Distance for contact max. 24 mm

 Contact arrangement
 View from termination side

 Panel cut out for inserts
 for use without
 hoods/housings


		Wire gauge	Part No.			
Identification		(mm ²)	Male contacts	Female contacts	Drawing	Dimensions in mm
Crimp contacts						
Power contacts						
silver plated		0.5	09 33 000 6121	09 33 000 6220		
		0.75	09 33 000 6114	09 33 000 6214		
		1.0	09 33 000 6105	09 33 000 6205		
		1.5	09 33 000 6104	09 33 000 6204		
		2.5	09 33 000 6102	09 33 000 6202		
		3	09 33 000 6106	09 33 000 6206		
	4	09 33 000 6107	09 33 000 6207			
gold plated		0.5	09 33 000 6122	09 33 000 6222		
		0.75	09 33 000 6115	09 33 000 6215		
		1.0	09 33 000 6118	09 33 000 6218		
		1.5	09 33 000 6116	09 33 000 6216		
		2.5	09 33 000 6123	09 33 000 6223		
		4.0	09 33 000 6119	09 33 000 6221		
Crimp contact identification						
Identification	Wire gauge			Stripping length		
no groove	0.5	mm ²	AWG 20	7.5 mm		
1 groove*	0.75	mm ²	AWG 18	7.5 mm		
1 groove	1	mm ²	AWG 18	7.5 mm		
2 grooves	1.5	mm ²	AWG 16	7.5 mm		
3 grooves	2.5	mm ²	AWG 14	7.5 mm		
wide groove	3.0	mm ²	AWG 12	7.5 mm		
no groove	4	mm ²	AWG 12	7.5 mm		
* on the back crimp collar						

* on the back crimp collar

Stock items in bold type