



Number of contacts

7 +



Inserts

		Part No.		Drawing	Dimensions in mm
Identification	Series	Male insert (M)	Female insert (F)		
Crimp terminal Order crimp contacts separately	Han D®	09 21 007 3031¹⁾	09 21 007 3131¹⁾		Contact arrangement View from termination side
¹⁾ Attention Only for thermoplastic hoods/housings					
Coding system with loss of contact 		09 33 000 9915			Use of the coding pin prevents incorrect mating to other connectors of the same type. The male pin should be omitted from the opposing cavity in the male insert.

		Wire gauge	Part No.		Drawing	Dimensions in mm																												
Identification	(mm ²)	Male contacts	Female contacts																															
Crimp contacts																																		
silver plated	0.14-0.37	09 15 000 6104	09 15 000 6204																															
	0.5	09 15 000 6103	09 15 000 6203																															
	0.75	09 15 000 6105	09 15 000 6205																															
	1.0	09 15 000 6102	09 15 000 6202																															
	1.5	09 15 000 6101	09 15 000 6201																															
	2.5	09 15 000 6106	09 15 000 6206																															
gold plated	0.14-0.37	09 15 000 6124	09 15 000 6224																															
	0.5	09 15 000 6123	09 15 000 6223																															
	0.75	09 15 000 6125	09 15 000 6225																															
	1.0	09 15 000 6122	09 15 000 6222																															
	1.5	09 15 000 6121	09 15 000 6221																															
	2.5	09 15 000 6126	09 15 000 6226																															
<table><thead><tr><th colspan="2">Wire gauge</th><th>ø</th><th>Stripping length</th></tr></thead><tbody><tr><td>0.14-0.37 mm²</td><td>AWG 26-22</td><td>0.90 mm</td><td>8 mm</td></tr><tr><td>0.5 mm²</td><td>AWG 20</td><td>1.10 mm</td><td>8 mm</td></tr><tr><td>0.75 mm²</td><td>AWG 18</td><td>1.30 mm</td><td>8 mm</td></tr><tr><td>1 mm²</td><td>AWG 18</td><td>1.45 mm</td><td>8 mm</td></tr><tr><td>1.5 mm²</td><td>AWG 16</td><td>1.75 mm</td><td>8 mm</td></tr><tr><td>2.5 mm²</td><td>AWG 14</td><td>2.25 mm</td><td>6 mm</td></tr></tbody></table>							Wire gauge		ø	Stripping length	0.14-0.37 mm ²	AWG 26-22	0.90 mm	8 mm	0.5 mm ²	AWG 20	1.10 mm	8 mm	0.75 mm ²	AWG 18	1.30 mm	8 mm	1 mm ²	AWG 18	1.45 mm	8 mm	1.5 mm ²	AWG 16	1.75 mm	8 mm	2.5 mm ²	AWG 14	2.25 mm	6 mm
Wire gauge		ø	Stripping length																															
0.14-0.37 mm ²	AWG 26-22	0.90 mm	8 mm																															
0.5 mm ²	AWG 20	1.10 mm	8 mm																															
0.75 mm ²	AWG 18	1.30 mm	8 mm																															
1 mm ²	AWG 18	1.45 mm	8 mm																															
1.5 mm ²	AWG 16	1.75 mm	8 mm																															
2.5 mm ²	AWG 14	2.25 mm	6 mm																															
FOC contacts for 1 mm plastic fibre																																		
		20 10 001 3212	20 10 001 3222																															

Stock items in bold type