



Product data sheet

Item No. 92.933.0053.1

Female connector with strain relief GST18I3F B2 ZR1 SW

Connector GST18i3, 3 pole, female, spring clamp connection, 250 V, 20 A, colour of coding: white, colour of housing: black



Item No.	92.933.0053.1
EAN	4015573402546
Order Unit	50 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Strain relief	Yes
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Black

Connection Data

Cable diameter	10.3 mm
Cable diameter 2	7.8 mm
Connection cross section solid	2.5 mm ²
Cross section solid 2	0.75 mm²
Connection cross section stranded max.	1.5 mm ²
Cross section stranded 2	0.75 mm²





Terminations per pole	2	
Model		
Model	female	
Connection type	Spring force	
Degree of protection (IP)	IP20	
Remark to type of connection	Fine stranded and stranded conductors require cable end sleeve	
Material		
Housing material	Polyamide	
Halogen free	Yes	
Contact material	CuZn	
Insulation components continous temperature	100 °C	
Surface finish	Tin-plated	
Dimensions		
Length	75 mm	

32.5 mm

15.5 mm

Technical drawing

Width

Height

