



Product data sheet

Item No. 92.934.0053.1

Male connector with strain relief GST18I3F S2 ZR1 SW

Connector GST18i3, 3 pole, male, spring clamp connection, 250 V, 20 A, colour of coding: black, colour of housing: black



Item No.	92.934.0053.1
EAN	4015573402560
Order Unit	50 Piece(s)

# Certificates / Approvals



### Technical data

## General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Strain relief	Yes
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Black

**Connection Data** 

Cable diameter	10.3 mm
Cable diameter 2	7.8 mm
Connection cross section solid	2.5 mm <sup>2</sup>
Cross section solid 2	0.75 mm²
Connection cross section stranded max.	1.5 mm <sup>2</sup>
Cross section stranded 2	0.75 mm²

# 💎 wieland



Terminations per pole	2			
Model				
Model	male			
Connection type	Spring force			
Degree of protection (IP)	IP20			
Remark to type of connection	Fine stranded and stranded conductors require cable end sleeve			
Material				
Housing material	Polyamide			
Halogen free	Yes			
Contact material	CuZn			
Insulation components continous temperature	100 °C			
Surface finish	Tin-plated			

#### Dimensions

Length	75 mm
Width	32.5 mm
Height	15.5 mm

### Technical drawing

