





Product details

CONNEC.WITH CABLE GST18I3K1BS 15 40SW

Extension cable, female - male, length 4m, GST18i3, 3 pole, 250V/16A, cable type H05VV, cross section 1,5 mm², color of coding: black, color of cable: black





Basic information

| Article number | 92.232.4000.1 |
|--------------------|---------------|
| EAN | 4015573326880 |
| Unit of measure | Piece |
| Packaging Quantity | 25 |

Classification

| Technical Classification | Cable assemblies |
|--------------------------|------------------|
| Wieland Product Families | H05VV-F3G1,5 PVC |

Design

| Besign | |
|---------------------------------|---------------------|
| Version of cable | Female - male |
| Cable type | H05VV-F |
| Cable type 2 | |
| Nominal cross section conductor | 1.5 mm ² |
| Cross section of cable 2 | |
| Number of poles | 3 |
| Number of poles 2 | |
| Degree of protection (IP) | IP40 |
| sheath strip length | |
| Sheath strip length 2 | |
| Wire strip length | |
| Insulation strip length 2 | |
| Preparation of conductor ends | |
| Design of conductor ends 2 | |
| Cable diameter | 8.3 mm |
| Cable diameter 2 | |
| Cable colour | Black |







Product details

| | | | | | | 4 _ |
|-----|------------|-----|---|----|-------------|-----|
| 1 - | Δr | וםו | - | | 1 21 | - |
| • | G I | 16 | | ·· | | Lo |

| Scheral Bata | |
|--|----------|
| Total length | 4 m |
| Rated voltage | 250 V |
| Rated voltage 2 | |
| Rated current | 16 A |
| Rated current 2 | |
| Mechanical coding | Yes |
| Marking of poles | L, N, PE |
| Color of coding/ contact carrier | Black |
| Color of coding 2/ contact carrier 2 | |
| Color of housing inclusive strain relief | Black |
| Interlockable | Yes |
| Pollution degree | 2 |
| Rated surge voltage | 4 kV |
| Rated impulse voltage 2 | |
| | |

Material

| Insulation components continous | 100 °C |
|-----------------------------------|------------|
| temperature | |
| Continuous temperature of cable | 70 °C |
| Continuous temperature of cable 2 | |
| Halogen free | No |
| Surface finish | Tin-plated |
| Surface coating of contacts 2 | |
| | |