

Data sheet

Commercial Art.No.: 92.030.6953.1

Distributor GST18i3V 3P1 B V SW

GST18i3 H-distributor, 3 pole, 1 IN, 3 OUT, with mounting option on separate mounting plate, coding mains 250 V, 20 A, coding color black



Commercial Art.No.	92.030.6953.1
EAN	4049088350733
Order Unit	1

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	self-locking (unlocking by tool)
Color of coding/ contact carrier	black
Marking of poles	L, N, PE

Model

Number of inputs	1
Number of outputs	3
Type of fastening	yes
Degree of protection (IP)	IP20
Type of distributor	H-distributor

Material

Housing material	Polyamide
halogen free	yes
Contact material	CuZn
Fire load	0 kWh
Insulation components continuous temperature	100 °C

Surface finish	Tin-plated
----------------	------------

Dimensions

Length	59 mm
Width	37.9 mm
Height	40 mm

Classification

ECLASS 11	
ECLASS 8.1	27440603
ETIM 7.0	EC002567
ETIM 6.0	EC002567
ETIM 5.0	EC002567
ETIM 4.0	EC002567

Product compliance

REACH-SVHC conformity status	Compliant
------------------------------	-----------