





LOGIC F1 A

213 47 112 A

AVAILABLE IN
ALU GREY 213 47 112 A



[View on website](#)

General info

LOCATION	exterior
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	round - 93
RECESSED DEPTH (MM)	40
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 24V-DC max.600kg

Electrical info

ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	non-dimmable
ENERGY CLASS	G

Lightsource info

Lightsource Name	LED
Lightsource	LED 0,6W / CRI>80 / 3000K / 45lm
LED Technics (light source)	45lm // 0,6W // 75lm/W
LED Technics (luminaire)	3lm // 1W // 5lm/W

Requirements








LED POWER SUPPLY 24V-DC

Options

GENIE BOX 90 R
CBOX

For detailed installation instructions, please consult the manual: [213_47_112_HAND.pdf](#)


FINISH YOUR SPECIFICATION

LED power supplies			#
	300 89 24 20	LED POWER SUPPLY 24V-DC / 20W	33 ☐
	300 89 24 40	LED POWER SUPPLY 24V-DC / 40W	66 ☐
	300 89 24 60	LED POWER SUPPLY 24V-DC / 60W	100 ☐
	300 89 24 61	LED POWER SUPPLY 24V-DC / 60W DIN	100 ☐
	300 89 24 80 ED1	LED POWER SUPPLY 24V-DC / 80W DIM1	133 ☐
	300 89 24 150	LED POWER SUPPLY 24V-DC / 150W	250 ☐
	21012 0160	LED POWER SUPPLY 24V-DC / 24W	40 ☐

LOGIC F1 A

213 47 112 A

Ground mounting boxes




Ø100
51
95
146
220
155

213 19 09 LOGIC 90 BOX R



Waterproof connection parts



140
140
15
173
101

216 12 00 CBOX



Notes: