





LOGIC MINI W R A

304 30 12 A

AVAILABLE IN
ALU GREY 304 30 12 A
WHITE 304 30 12 W



[View on website](#)



General info

LOCATION	interior-exterior
INSTALLATION	Wall Recessed
CUTOUT SHAPE/SIZE (MM)	round - 55
RECESSED DEPTH (MM)	50
THICKNESS OF MOUNTING SURFACE (MM)	min.12
INGRESS PROTECTION	IP54
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 24V-DC

Electrical info

ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	non-dimmable
ENERGY CLASS	G

Lightsource info

Lightsource Name	LED
Lightsource	LED 0,6W / 3000K / 40lm
LED Technics (light source)	40lm // 0,6W // 67lm/W
LED Technics (luminaire)	4lm // 1W // 5lm/W

Requirements

LED POWER SUPPLY 24V-DC

Options








CONCRETE BOX 188

For detailed installation instructions, please consult the manual: [304_30_12_HAND.pdf](#)

LOGIC MINI W R A

304 30 12 A

FINISH YOUR SPECIFICATION

LED power supplies			#
	300 89 24 20	LED POWER SUPPLY 24V-DC / 20W	30 ☐
	300 89 24 40	LED POWER SUPPLY 24V-DC / 40W	60 ☐
	300 89 24 60	LED POWER SUPPLY 24V-DC / 60W	90 ☐
	300 89 24 61	LED POWER SUPPLY 24V-DC / 60W DIN	90 ☐
	300 89 24 80 ED1	LED POWER SUPPLY 24V-DC / 80W DIM1	120 ☐
	300 89 24 150	LED POWER SUPPLY 24V-DC / 150W	225 ☐
	21012 0160	LED POWER SUPPLY 24V-DC / 24W	36 ☐

LOGIC MINI W R A

304 30 12 A

Concrete boxes



Notes: