





LOGIC 90 R A 93055 ANO

213 48 811 933 ANO

AVAILABLE IN

ALU ANODIZED 213 48 811 933 ANO

BLACK 213 48 811 933 B



[View on website](#)

General info

LOCATION	exterior
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	round - 93
RECESSED DEPTH (MM)	125
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.CABLE H05 RN-F 2 x 1mm ² 0,5m REFLECTOR WFL-55° INCL.LED POWER SUPPLY 350mA-DC INCL.IP68 CONNECTOR 3P IEC 60598-2-13 : max.150kg 25N/cm ² ESG 5mm BLACK = BLACK ANODISED

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY INCLUDED	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E

Lightsource info

Lightsource Name	LED
Lightsource	LED array 7,1W / CRI>90 (R9: 52) / 3000K / 812lm
TM-30 Values	Rf: 90 / Rg: 99
SDCM	SDCM2
Riskgroup	RG1
LM80	L90B10 > 50000
LED Technics (light source)	812lm // 7,1W // 115lm/W
LED Technics (luminaire)	710lm // 8W // 87lm/W

Options

LOGIC 90 BOX R
CBOX


LOGIC 90 R A 93055 ANO

213 48 811 933 ANO

For detailed installation instructions, please consult the manual: [213_48_811_XXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Ground mounting boxes




213 19 09

LOGIC 90 BOX R

☐

Waterproof connection parts



216 12 00

CBOX

☐

Notes: