





DEEP VARO 92736 S1 W

423 021 811 922 W

AVAILABLE IN

BLACK 423 021 811 922 B

WHITE 423 021 811 922 W



[View on website](#)



General info

LOCATION	interior
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 76
RECESSED DEPTH (MM)	90
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-36° EXCLLED POWER SUPPLY 350mA-DC

Electrical info

CLASS	III
ENERGY CLASS	E

Lightsource info

Lightsource Name	LED
Lightsource	LED array 7,1W / CRI>90 (R9: 60) / 2700K / 779lm
TM-30 Values	Rf: 89 / Rg: 100
SDCM	SDCM2
Riskgroup	RG1
LM80	L90B10 > 50000
LED Technics (light source)	779lm // 7,1W // 110lm/W
LED Technics (luminaire)	671lm // 8W // 82lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

Options

PLASTERKIT 101

DEEP VARO 92736 S1 W

423 021 811 922 W

For detailed installation instructions, please consult the manual: [423_021_811_9X2_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	 PLASTERKIT 101 Required
 Wood	-
 Concrete + plaster	 PLASTERKIT 101 Required
 Lintel + plaster	 PLASTERKIT 101 Required
 Hollow-core slab + plaster	 PLASTERKIT 101 Required
 Stretched ceiling	-


DEEP VARO 92736 S1 W

423 021 811 922 W

FINISH YOUR SPECIFICATION

LED power supplies


#



300 90 91

LED POWER SUPPLY 350mA-DC / 15W


2 (1)

☐


300 90 108 U

LED POWER SUPPLY 350mA-DC / 8W


1 (1)

☐


300 90 110

LED POWER SUPPLY 350mA-DC / 10W DIM8

1

☐


300 90 116

LED POWER SUPPLY 350mA-DC / 18W DIM8


2->2

☐


300 90 124

LED POWER SUPPLY MULTI-POWER DIM7


2 (2)

☐


300 90 125

LED POWER SUPPLY MULTI-POWER MINI DIM5

2 (2)

☐


21012 0258

LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8


1

☐

DEEP VARO 92736 S1 W

423 021 811 922 W

Plasterkits



202 11 19 PLASTERKIT 101



Notes: