





LOGIC 60 R 24V 93020 ANO

13960 9320 ANO

AVAILABLE IN
ALU ANODIZED 13960 9320 ANO



[View on website](#)



General info

LOCATION	exterior
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	round - 61
RECESSED DEPTH (MM)	100
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-20° INCL.1 x CABLE H05 RN-F 2 x 1mm ² 0,5m EXCL.LED POWER SUPPLY 24V-DC (non-dimmable or dimmable with PWM output) IEC 60598-2-13 : max.150kg 25N/cm ² ESG 5mm

Electrical info

ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	non-dimmable
ENERGY CLASS	E

Lightsource info

Lightsource Name	LED
Lightsource	LED array 7,1W / CRI>90 (R9: 52) / 3000K / 812lm
TM-30 Values	Rf: 90 / Rg: 99
SDCM	SDCM2
Riskgroup	RG1
LM80	L90B10 > 50000
LED Technics (light source)	812lm // 7,1W // 115lm/W
LED Technics (luminaire)	750lm // 8W // 92lm/W

Requirements

LED POWER SUPPLY 24V-DC

LOGIC 60 R 24V 93020 ANO

13960 9320 ANO

Options

LOGIC 60 BOX R

CBOX

IP68 CONNECTION KIT

IP68 CONNECTOR 3P

For detailed installation instructions, please consult the manual: [13960_XXX0_HAND.pdf](#)


LOGIC 60 R 24V 93020 ANO

13960 9320 ANO

FINISH YOUR SPECIFICATION


LED power supplies

#



300 89 24 150 LED POWER SUPPLY 24V-DC / 150W

21


☐

21012 0160 LED POWER SUPPLY 24V-DC / 24W

3

☐


Control gear, ballast and transformers



21032 0320 AMBIENT LIGHT SENSOR & 24V DIMMER (PWM)

☐

Ground mounting boxes




213 19 10 LOGIC 60 BOX R

☐


LOGIC 60 R 24V 93020 ANO

13960 9320 ANO


Waterproof connection parts



216 12 00 CBOX

☐

216 12 01 IP68 CONNECTION KIT

☐

216 12 02 IP68 CONNECTOR 3P

☐

Notes: