





LOGIC 90 R A 24V 93055 ANO

13966 9330 ANO

AVAILABLE IN
ALU ANODIZED 13966 9330 ANO
BLACK 13966 9330 B



[View on website](#)

General info

LOCATION	exterior
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	round - 93
RECESSED DEPTH (MM)	125
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.CABLE H05 RN-F 2 x 1mm ² 0,5m REFLECTOR WFL-55° EXCL.LED POWER SUPPLY 24V-DC (non-dimmable or dimmable with PWM output) INCL.IP68 CONNECTOR 3P IEC 60598-2-13 : max.150kg 25N/cm ² ESG 5mm BLACK = BLACK ANODISED

Electrical info

ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	non-dimmable
ENERGY CLASS	E

Lightsource info

Lightsource Name	LED
Lightsource	LED array 7,1W / CRI>90 (R9: 52) / 3000K / 812lm
TM-30 Values	Rf: 90 / Rg: 99
SDCM	SDCM2
Riskgroup	RG1
LM80	L90B10 > 50000
LED Technics (light source)	812lm // 7,1W // 115lm/W
LED Technics (luminaire)	710lm // 8W // 87lm/W

Requirements

LED POWER SUPPLY 24V-DC

LOGIC 90 R A 24V 93055 ANO

13966 9330 ANO

Options

LOGIC 90 BOX R

CBOX

For detailed installation instructions, please consult the manual: [13966_XXX0_HAND.pdf](#)


LOGIC 90 R A 24V 93055 ANO

13966 9330 ANO

FINISH YOUR SPECIFICATION


LED power supplies

#



300 89 24 150 LED POWER SUPPLY 24V-DC / 150W

21


☐


21012 0160 LED POWER SUPPLY 24V-DC / 24W

3

☐


Control gear, ballast and transformers



21032 0320 AMBIENT LIGHT SENSOR & 24V DIMMER (PWM)

☐


Ground mounting boxes



213 19 09 LOGIC 90 BOX R

☐

Waterproof connection parts



216 12 00 CBOX

☐



LOGIC 90 R A 24V 93055 ANO

13966 9330 ANO

Notes: