





DEEP VARO AC 92733 DIM8 W

21927 9228 W

AVAILABLE IN

BLACK 21927 9228 B

WHITE 21927 9228 W



[View on website](#)



General info

LOCATION	interior
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 76
RECESSED DEPTH (MM)	100
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33°

Electrical info

ELECTRICAL	230V / 50-60Hz
CLASS	I
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	F

Lightsource info

Lightsource Name	LED
Lightsource	AC LED array 8W / CRI>90 (R9: 55) / 2700K / 597lm
TM-30 Values	Rf: 92 / Rg: 98
SDCM	SDCM3
Riskgroup	RG1
LM80	L80B10 > 67000
LED Technics (light source)	597lm // 8W // 75lm/W
LED Technics (luminaire)	510lm // 8W // 64lm/W

Options

PLASTERKIT 101

For detailed installation instructions, please consult the manual: [21927_XXX8_HAND.pdf](#)

DEEP VARO AC 92733 DIM8 W

21927 9228 W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	 PLASTERKIT 101 Required
 Wood	-
 Concrete + plaster	 PLASTERKIT 101 Required
 Lintel + plaster	 PLASTERKIT 101 Required
 Hollow-core slab + plaster	 PLASTERKIT 101 Required
 Stretched ceiling	-

FINISH YOUR SPECIFICATION

Plasterkits



202 11 19 PLASTERKIT 101

☐

Notes: