

KLLSB

Courbe intérieure pour KLL



A fixer avec:



Boulon et écrou autobloquant
VM

Rayon: 300 mm

Exec. Std.

Sendzimir

Mat. Opt.

Galvanisé à chaud

Mat. Opt. PE

Revêtement en poudre

HD	Référence	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Magasin	Unité
HD	KLLSB60.150	60	146			1,528	1		STK
HD	KLLSB60.200	60	196			1,629	1		STK
HD	KLLSB60.300	60	296			1,830	1		STK
HD	KLLSB60.400	60	396			2,032	1		STK
HD	KLLSB60.450	60	443			2,133	1		STK
HD	KLLSB60.500	60	496			2,234	1		STK
HD	KLLSB60.600	60	596			2,435	1		STK
HD	KLLSB85.150	85	145			1,922	1		STK
HD	KLLSB85.200	85	196			2,083	1		STK
HD	KLLSB85.300	85	296			2,284	1		STK
HD	KLLSB85.400	85	396			2,486	1		STK
HD	KLLSB85.450	85	445			2,587	1		STK
HD	KLLSB85.500	85	496			2,688	1		STK
HD	KLLSB85.600	85	596			2,889	1		STK
HD	KLLSB110.150	110	145			2,934	1		STK
HD	KLLSB110.200	110	196			2,755	1		STK
HD	KLLSB110.300	110	296			2,956	1		STK
HD	KLLSB110.400	110	396			3,158	1		STK
HD	KLLSB110.450	110	445			3,259	1		STK
HD	KLLSB110.500	110	496			3,360	1		STK
HD	KLLSB110.600	110	596			3,561	1		STK

Nombre minimal des boulons et des écrous VM6.10: 8 pièces.