



KLLT

T-stuk voor KLL



Te bevestigen met:



Zelfborgende moer en bout
VM

Radius: 300 mm

Stand. Uitv.

Sendzimir

Mat. Opt.

Hot-Dip

Mat. Opt. PE

Poedercoating

	150	200	300	400	500	600
A	1021	1071	1171	1271	1371	1471

HD	Artikel	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Stock	Eenh.
HD	KLLT60.150	60	141			2,229	1		STK
HD	KLLT60.200	60	191			2,821	1		STK
HD	KLLT60.300	60	291			3,447	1		STK
HD	KLLT60.400	60	391			3,882	1		STK
HD	KLLT60.450	60	443			4,099	1		STK
HD	KLLT60.500	60	491			4,317	1		STK
HD	KLLT60.600	60	591			4,753	1		STK
HD	KLLT85.150	85	145			2,623	1		STK
HD	KLLT85.200	85	195			3,484	1		STK
HD	KLLT85.300	85	295			4,134	1		STK
HD	KLLT85.400	85	395			4,594	1		STK
HD	KLLT85.450	85	445			4,824	1		STK
HD	KLLT85.500	85	495			5,054	1		STK
HD	KLLT85.600	85	595			5,514	1		STK
HD	KLLT110.150	110	145			3,635	1		STK
HD	KLLT110.200	110	195			4,131	1		STK
HD	KLLT110.300	110	295			4,806	1		STK
HD	KLLT110.400	110	395			5,290	1		STK
HD	KLLT110.450	110	445			5,533	1		STK
HD	KLLT110.500	110	495			5,775	1		STK
HD	KLLT110.600	110	595			6,260	1		STK

Minimum aantal bouten en moeren VM6.10: 12 stuks.