


# KLLT

## Pièce en T pour KLL



**A fixer avec:**



Boulon et écrou autobloquant  
VM

Rayon: 300 mm

Exec. Std.

Sendzimir

Mat. Opt.

Galvanisé à chaud

Mat. Opt. PE

Revêtement en poudre

|   | 150  | 200  | 300  | 400  | 500  | 600  |
|---|------|------|------|------|------|------|
| A | 1021 | 1071 | 1171 | 1271 | 1371 | 1471 |

| HD | Référence          | ↑↓<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦 | Magasin | Unité |
|----|--------------------|----------|---------|------------|---------|--------|---|---------|-------|
| HD | <b>KLLT60.150</b>  | 60       | 141     |            |         | 2,229  | 1 |         | STK   |
| HD | <b>KLLT60.200</b>  | 60       | 191     |            |         | 2,821  | 1 |         | STK   |
| HD | <b>KLLT60.300</b>  | 60       | 291     |            |         | 3,447  | 1 |         | STK   |
| HD | <b>KLLT60.400</b>  | 60       | 391     |            |         | 3,882  | 1 |         | STK   |
| HD | <b>KLLT60.450</b>  | 60       | 443     |            |         | 4,099  | 1 |         | STK   |
| HD | <b>KLLT60.500</b>  | 60       | 491     |            |         | 4,317  | 1 |         | STK   |
| HD | <b>KLLT60.600</b>  | 60       | 591     |            |         | 4,753  | 1 |         | STK   |
| HD | <b>KLLT85.150</b>  | 85       | 145     |            |         | 2,623  | 1 |         | STK   |
| HD | <b>KLLT85.200</b>  | 85       | 195     |            |         | 3,484  | 1 |         | STK   |
| HD | <b>KLLT85.300</b>  | 85       | 295     |            |         | 4,134  | 1 |         | STK   |
| HD | <b>KLLT85.400</b>  | 85       | 395     |            |         | 4,594  | 1 |         | STK   |
| HD | <b>KLLT85.450</b>  | 85       | 445     |            |         | 4,824  | 1 |         | STK   |
| HD | <b>KLLT85.500</b>  | 85       | 495     |            |         | 5,054  | 1 |         | STK   |
| HD | <b>KLLT85.600</b>  | 85       | 595     |            |         | 5,514  | 1 |         | STK   |
| HD | <b>KLLT110.150</b> | 110      | 145     |            |         | 3,635  | 1 |         | STK   |
| HD | <b>KLLT110.200</b> | 110      | 195     |            |         | 4,131  | 1 |         | STK   |
| HD | <b>KLLT110.300</b> | 110      | 295     |            |         | 4,806  | 1 |         | STK   |
| HD | <b>KLLT110.400</b> | 110      | 395     |            |         | 5,290  | 1 |         | STK   |
| HD | <b>KLLT110.450</b> | 110      | 445     |            |         | 5,533  | 1 |         | STK   |
| HD | <b>KLLT110.500</b> | 110      | 495     |            |         | 5,775  | 1 |         | STK   |
| HD | <b>KLLT110.600</b> | 110      | 595     |            |         | 6,260  | 1 |         | STK   |

Nombre minimal des boulons et des écrous VM6.10: 12 pièces.