

PRODUCT-DETAILS

## JSHD4-2-AH

# JSHD4-2-AH Three-position handheld device - Complete



### Algemene informatie

Type	JSHD4-2-AH
Artikelnummer	2TLA019995R0800
EAN	7350024453423
Omschrijving	JSHD4-2-AH Three-position handheld device - Complete
Omschrijving	<p>The JSHD4-2-AH is an ergonomic three-position device which top part has LEDs, a front button and a top button, and which bottom part is equipped with a cable gland and a PCB with 10 screw connections.</p> <p>Three-position devices are used to allow a limited movement of the machine when the operator is in the dangerous area, for example during troubleshooting, test running and programming.</p>

### Additional Information

Productnaam	Three-position handheld device - Complete
Functie	Three-position device used to allow a limited movement of the machine when the operator is in the dangerous area.
Subfunctie	1 front and 1 top auxiliary buttons
Statusindicator	Yes

### Safety Information

Prestatieniveau (PL)	Up to e
B10d-waarde	2 million operations to middle position 968 000 operations to bottom position

## Technical

Uitvoering van de interface	Contacts
Verbindingsconfiguratie	Cable gland and 10 screw connection
Aantal contacten CO	2
Aantal contacten NC	0
Aantal contacten NO	0
Maximale schakelstroom	Main Circuit 0.02 mA
Maximaal schakelvoltage	Main Circuit 30 V
Minimale schakelcapaciteit	Main Circuit 8 mA, 10 VDC
Nominale bedrijfsstroom DC-12 (I <sub>e</sub> )	(24 V) 0.02 A
Nominaal bedrijfsvoltage	24 V DC
Technische informatie	Operating force: Approx. 15 N for three-position button (ON), Approx. 45 N for three-position button (OFF), Approx. 2.5 N for top/front pushbutton; Mechanical service life: 1 million cycles, top to middle position, 100 000 cycles, middle to bottom position, and top/front push button

## Environmental

Beschermingsgraad	IP65
Omgevingsluchttemperatuur	Operation -10 ... +70 °C
Materiaal	Handle: Polyamide and Noryl Rubber: Neoprene

## Technical UL/CSA

Behuizingstype UL/CSA	1
-----------------------	---

## Popular Downloads

Gegevensblad, technische informatie	2TLC010001C0202
Instructies en handleidingen	2TLC172072M0201
Schakelschema	2TLC010143D0201

## Certificates and Declarations (Document Number)

CSA-certificaat	2TLC172086D0201
Conformiteitsverklaring - CE	2TLC172022D0201
Declaration of Conformity - UKCA	2TLC010152D0201
Instructies en handleidingen	2TLC172072M0201
SEMKO-certificaat	2TLC172032D0201

## Dimensions

Product netto breedte	34 mm
Product netto diepte	60 mm
Product netto hoogte	254 mm

Product netto gewicht 0.314 kg

### Ordering

Minimale bestelhoeveelheid	1 stuk
Nummer douanetarief	85369095

### Classifications

Object classificatiecode	B
ETIM 6	EC002571 - Toestemmings-/validatieschakelaar
ETIM 7	EC002571 - Agreement switch
ETIM 8	EC002571 - Agreement switch
eClass	V11.0 : 27371238

### Categorieën

Laagspanningsproducten en -systemen → Control Producten → Veiligheidsproducten → Veiligheidsbedieningen → JSHD

