

PRODUCT-DETAILS

6131/31-24-500

6131/31-24-500 KNX Presence Premium W



Algemene informatie

Type	6131/31-24-500
Artikelnummer	2CKA006132A0348
EAN	4011395185940
Omschrijving	6131/31-24-500 KNX Presence Premium W

Omschrijving	Detection range (for mounting height 2.5 m, 3 m and 4 m): circular. Seated persons Ø: max. 8 m, max. 10 m and max. 14 m. Walking persons Ø: max. 10 m, max. 12 m and max. 16 m. Visible height 23 mm. With 4 channels. For dimming/brightness of the rules to a defined value in a designated collection area. HVAC function for controlling heating and/or cooling systems and ventilation systems in the designated collection area. Detectors application with 2 power off stages. Detectors application with integrated monitoring function. Constant light controller with up to two independent channels. Constant light controller with max. 2 outputs for dimming daylight control/rules of two rooflights in the room. Integrated object room temperature controller. 10 freely programmable IR channels (blue and/or white) Incl. 5 logic channels (logic gates, gates, delay and staircase lighting) Evaluation via internal brightness sensor. Weighting of up to 2 external brightness values and the internal brightness sensor possible. The programming button can be activated with the IR transmitter 6010-25 (-500). With integrated KNX bus coupler. Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm. Suitable for surface mounting installation. Cannot be installed in British Standard or VDE flushmounted box. Recommendation: Installation housing from Kaiser HaloX-O (Art.no. 1290-40) with corresponding cover plates (1290-47 or 1290-85 for fair faced concrete) or IBTronic H120-68 from Spelsberg.
--------------	--

Ordering

EAN	4011395185940
Nummer douanetarief	85365080
Minimale bestelhoeveelheid	1 stuk
E-Number (Finland)	2815473

E-Number (Sweden)	1738688
-------------------	---------

Dimensions

Product netto gewicht	81 g
-----------------------	------

Container Information

Pakketniveau 1 Units	1 stuk
Pakketniveau 1 EAN	4011395185940
Pakketniveau 1 Lengte	121 mm
Pakketniveau 1 Hoogte	62 mm
Pakketniveau 1 Breedte	96 mm
Pakketniveau 1 Bruto gewicht	0.146 kg

Technical

Omgevingsluchttemperatuur	Operation -5 ... +45 °C
Compatibele bussystemen	KNX (TP)
Beschermingsgraad	IP20
Montagetype	Surface mounted (plaster)

Certificates and Declarations (Document Number)

Gegevensblad, technische informatie	2CKA001373B8668
Conformiteitsverklaring - CE	2CKA100000E1059
Instructies en handleidingen	No document needed
REACH Declaration	2CKA309999E9999
RoHS-informatie	9AKK104295D8727

Environmental

RoHS-status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

Classifications

ETIM 7	EC001582 - Movement sensor for bus system
ETIM 8	EC001582 - Movement sensor for bus system
eClass	V11.0 : 27143144
WEEE-categorie	5. Small Equipment (No External Dimension More Than 50 cm)

Categorieën

Laagspanningsproducten en -systemen → Gebouwautomatisering → KNX → Aanwezigheidsdetectie → Aanwezigheidssensoren

