

## PRODUCT-DETAILS

# 6131/31-24-500

## 6131/31-24-500 KNX Presence Premium W



### Informations générales

|                              |                                       |
|------------------------------|---------------------------------------|
| Extension du type de produit | 6131/31-24-500                        |
| Code de produit              | 2CKA006132A0348                       |
| EAN                          | 4011395185940                         |
| Description courte           | 6131/31-24-500 KNX Presence Premium W |

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description longue | <p>Detection range (for mounting height 2.5 m, 3 m and 4 m): circular. Seated persons Ø: max. 8 m, max. 10 m and max. 14 m. Walking persons Ø: max. 10 m, max. 12 m and max. 16 m. Visible height 23 mm. With 4 channels. For dimming/brightness of the rules to a defined value in a designated collection area. HVAC function for controlling heating and/or cooling systems and ventilation systems in the designated collection area. Detectors application with 2 power off stages. Detectors application with integrated monitoring function. Constant light controller with up to two independent channels. Constant light controller with max. 2 outputs for dimming daylight control/rules of two rooflights in the room. Integrated object room temperature controller. 10 freely programmable IR channels (blue and/or white) Incl. 5 logic channels (logic gates, gates, delay and staircase lighting) Evaluation via internal brightness sensor. Weighting of up to 2 external brightness values and the internal brightness sensor possible. The programming button can be activated with the IR transmitter 6010-25 (-500). With integrated KNX bus coupler. Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm. Suitable for surface mounting installation. Cannot be installed in British Standard or VDE flushmounted box. Recommendation: Installation housing from Kaiser HaloX-O (Art.no. 1290-40) with corresponding cover plates (1290-47 or 1290-85 for fair faced concrete) or IBTronic H120-68 from Spelsberg.</p> |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Commande

|     |               |
|-----|---------------|
| EAN | 4011395185940 |
|-----|---------------|

|                    |          |
|--------------------|----------|
| Code douanier      | 85365080 |
| Quantité minimum   | 1 pièce  |
| E-Number (Finland) | 2815473  |
| E-Number (Sweden)  | 1738688  |

---

## Dimensions

---

|           |      |
|-----------|------|
| Poids net | 81 g |
|-----------|------|

---

---

## Emballage

---

|                             |               |
|-----------------------------|---------------|
| Emballage Niveau 1 Unités   | 1 pièce       |
| Emballage Niveau 1 EAN      | 4011395185940 |
| Emballage Niveau 1 Longueur | 121 mm        |
| Emballage Niveau 1 Hauteur  | 62 mm         |
| Emballage Niveau 1 Largeur  | 96 mm         |
| Emballage Niveau 1 Poids    | 0.146 kg      |

---

---

## Technique

---

|                              |                           |
|------------------------------|---------------------------|
| Température de l'air ambiant | Operation -5 ... +45 °C   |
| Compatible Bus Systems       | KNX (TP)                  |
| Indice de protection         | IP20                      |
| Type de montage              | Surface mounted (plaster) |

---

---

## Certificats et Déclarations (Numéro de document)

---

|                                        |                    |
|----------------------------------------|--------------------|
| Fiche produit, informations techniques | 2CKA001373B8668    |
| Déclaration de Conformité - CE         | 2CKA100000E1059    |
| Instructions et manuels                | No document needed |
| REACH Declaration                      | 2CKA309999E9999    |
| Informations RoHS                      | 9AKK104295D8727    |

---

---

## Environnement

---

|             |                                                                 |
|-------------|-----------------------------------------------------------------|
| Statut RoHS | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
|-------------|-----------------------------------------------------------------|

---

---

## Classifications

---

|        |                                           |
|--------|-------------------------------------------|
| ETIM 7 | EC001582 - Movement sensor for bus system |
| ETIM 8 | EC001582 - Movement sensor for bus system |

|                |                                                            |
|----------------|------------------------------------------------------------|
| eClass         | V11.0 : 27143144                                           |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |

---

Catégories

---

Produits basse tension → Home and Building Automation → KNX → Presence Detection → Presence Detectors

