

PRODUCT-DETAILS

6131/20-24-500

6131/20-24-500 KNX Presence Mini W



Informations générales

Extension du type de produit	6131/20-24-500
Code de produit	2CKA006132A0342
EAN	4011395185889
Description courte	6131/20-24-500 KNX Presence Mini W

Description longue	Detection range (for mounting height 2.5 m, 3 m and 4 m): circular. Seated persons Ø: max. 5 m, max. 6.5 m and max. 9 m. Walking persons Ø: max. 6.5 m, max. 8 m and max. 10.5 m. Visible height 16 mm. With 2 channels. Targeted for connection and disconnection of lights bands depending on the room brightness. Regulation in response to the movement possible. Using the device as presence and/or movement detectors. Detectors application with 2 power off stages. Detectors application with integrated monitoring function. Constant light switch with up to two independent channels. Constant light switch with max. 2 outputs for brightness-dependent switching of two light bands in the area. With integrated KNX bus coupler. Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm. Suitable for surface mounting installation. Cannot be installed in British Standard or VDE flushmounted box. Recommendation: Installation housing from Kaiser HaloX-O (Art.no. 1290-40) with corresponding cover plates (1290-47 or 1290-85 for fair faced concrete) or IBTronic H120-68 from Spelsberg.
--------------------	--

Commande

EAN	4011395185889
Code douanier	85365080
Quantité minimum	1 pièce
E-Number (Finland)	2815467

E-Number (Sweden)	1738685
-------------------	---------

Dimensions

Poids net	72 g
-----------	------

Emballage

Emballage Niveau 1 Unités	1 pièce
Emballage Niveau 1 EAN	4011395185889
Emballage Niveau 1 Longueur	125 mm
Emballage Niveau 1 Hauteur	90 mm
Emballage Niveau 1 Largeur	115 mm
Emballage Niveau 1 Poids	0.131 kg

Technique

Température de l'air ambiant	Operation -5 ... +45 °C
Compatible Bus Systems	KNX (TP)
Indice de protection	IP20
Type de montage	Surface mounted (plaster)

Certificats et Déclarations (Numéro de document)

Fiche produit, informations techniques	2CKA001373B8668
Déclaration de Conformité - CE	2CKA100000E1053
Instructions et manuels	DEBJE-6132-0-0342
REACH Declaration	2CKA309999E9999
Informations RoHS	9AKK104295D8727

Environnement

Statut RoHS	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

Classifications

ETIM 7	EC001582 - Movement sensor for bus system
ETIM 8	EC001582 - Movement sensor for bus system
eClass	V11.0 : 27143144
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)

Catégories

Produits basse tension → Home and Building Automation → KNX → Presence Detection → Presence Detectors

