

PRODUCT-DETAILS

6131/50-24-500

6131/50-24-500 KNX Presence Cor. W



Informations générales

Extension du type de produit	6131/50-24-500
Code de produit	2CKA006132A0399
EAN	4011395216446
Description courte	6131/50-24-500 KNX Presence Cor. W

Description longue	Detection range: rectangular. For mounting height of 3 m: frontal toward the detector at a max. of 20 m x 3 m (at a max. of 10 m x 3 m per side). Crosswise toward the detector at a max. of 30 m x 3 m (max. of 15 m x 3m per side). With integrated KNX bus coupler. Mounting height 27 mm. With 2 channels. Targeted for connection and disconnection of lights bands depending on the room brightness. Regulation in response to the movement possible. Using the device as presence and/or movement detectors. Detectors application with 2 power off stages. Detectors application with integrated monitoring function. Constant light switch with up to two independent channels. Constant light switch with max. 2 outputs for brightness-dependent switching of two light bands in the area. Ceiling mounting on suspended ceilings with spring clamps, on solid ceilings in surface-mounting boxes 6131/39-xxx(-500) or on VDE flush-mounted boxes with intermediate ring for VDE flush-mounted boxes 6131/38-xxx(-500). Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm. Cannot be installed in British Standard or VDE flushmounted box. Recommendation: Installation housing from Kaiser HaloX-O (Art.no. 1290-40) with corresponding cover plates (1290-47 or 1290-85 for fair faced concrete) or IBTronic H120-68 from Spelsberg.
--------------------	---

Commande

EAN	4011395216446
Code douanier	85365080

Quantité minimum	1 pièce
E-Number (Finland)	2815600
E-Number (Sweden)	1739146

Dimensions

Poids net	116.5 g
-----------	---------

Emballage

Emballage Niveau 1 Unités	1 pièce
Emballage Niveau 1 EAN	4011395216446
Emballage Niveau 1 Longueur	121 mm
Emballage Niveau 1 Hauteur	62 mm
Emballage Niveau 1 Largeur	96 mm
Emballage Niveau 1 Poids	0.157 kg

Technique

Température de l'air ambiant	Operation -5 ... +45 °C
Compatible Bus Systems	KNX (TP)
Indice de protection	IP20
Type de montage	Surface mounted (plaster)

Certificats et Déclarations (Numéro de document)

Fiche produit, informations techniques	2CKA001373B8668
Déclaration de Conformité - CE	2CKA100000E1102
Instructions et manuels	No document needed
REACH Declaration	2CKA309999E9999
Informations RoHS	9AKK104295D8727

Environnement

Statut RoHS	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

Classifications

ETIM 7	EC001582 - Movement sensor for bus system
ETIM 8	EC001582 - Movement sensor for bus system
eClass	V11.0 : 27143144

Catégorie DEEE

5. Small Equipment (No External Dimension More Than 50 cm)

Catégories

Produits basse tension → Home and Building Automation → KNX → Presence Detection → Presence Detectors

