

PRODUCT-DETAILS

UD/S4.210.2.1

UD/S4.210.2.1 LED-Dim actuator 4x210W



Algemene informatie

Type	UD/S4.210.2.1
Artikelnummer	2CKA006197A0047
EAN	4011395251867
Omschrijving	UD/S4.210.2.1 LED-Dim actuator 4x210W

Omschrijving	Multichannel universal dimming actuator optimised for dimming retrofit LED lamps (LEDi). Also suitable for dimming incandescent lamps, low-voltage halogen lights with conventional or electronic transformers, 230 V halogen lamps and dimmable energy-saving halogen lamps. Automatic load detection (can be deactivated). Separate N-connection per channel. Parallel connection of the outputs possible to increase the output power. Outputs can be connected in parallel in any configuration. Minimum load: 2 W. Manual operation on device also possible without bus voltage or in an unprogrammed status. Programming of the device also possible without applied 230V supply voltage. Extensive test and diagnosis functions for the i-Bus tool. Fast parameter setting in ETS using copyable channel templates. With integrated bus coupler. Nominal power at 230 V~ mains voltage: 230 V~ incandescent and halogen lamps: 4 x 210 W/VA to 1 x 600 W/VA. Dimmable 230 V~ LEDi: 4 x 210 W/VA to 1 x 600 W/VA in trailing edge control, 4 x 80 W/VA to 1 x 200 W/VA in leading edge control. Inductive L-transformers with LED/low-voltage halogen lamp: 4 x 210 W/VA to 1 x 600 W/VA. Electronic C-transformers with LED/low-voltage halogen lamp: 4 x 210 W/VA to 1 x 600 W/VA. Electronic LC-transformers with LED/low-voltage halogen lamp: 4 x 80 W/VA to 1 x 200 W/VA.
--------------	--

Ordering

EAN	4011395251867
Nummer douanetarief	85389091
Minimale bestelhoeveelheid	1 stuk

E-Number (Finland)	2814591
E-Number (Sweden)	1739490

Dimensions

Product netto gewicht	283 g
-----------------------	-------

Container Information

Pakketniveau 1 Units	1 stuk
Pakketniveau 1 EAN	4011395251867
Pakketniveau 1 Lengte	150 mm
Pakketniveau 1 Hoogte	96 mm
Pakketniveau 1 Breedte	125 mm
Pakketniveau 1 Brutogewicht	0.283 kg

Technical

Omgevingsluchttempera- tuur	Operation -5 ... +45 °C
Compatibele bussystemen	KNX (TP)
Beschermingsgraad	IP20
Montagetype	DIN-Rail
Breedte in module- eenheden	80

Certificates and Declarations (Document Number)

Gegevensblad, technische informatie	No document needed
Conformiteitsverklaring - CE	2CKA100000E2617
Instructies en handleidingen	2CKA000073B9628
RoHS-informatie	9AKK104295D8727

Environmental

RoHS-status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

Classifications

ETIM 7	EC001094 - Dimming actuator for bus system
ETIM 8	EC001094 - Dimming actuator for bus system
eClass	V11.0 : 27143123
WEEE-categorie	5. Small Equipment (No External Dimension More Than 50 cm)

Categorieën

Laagspanningsproducten en -systemen → Gebouwautomatisering → KNX → Lichtbediening → Universele dimmeraandrijvingen

