

Enclosure-NSVE

INFORMATION

NSVE is designed to allow access during installation from the front and the sides, since side panels are removable. The enclosure is wall-mounted using a special assembly brace and holes on the back panel. The series is available in heights of 6, 10, 15, and 21 U with a depth of 465 mm. Heights 10, 15, and 21 U are also available with a depth of 635 mm. The enclosure is made of bent sheet steel. At the top and bottom is an adjustable cable gland with foam plastic to seal out dust and the option of either forced air ventilation or self-ventilation. The enclosure is intended for indoor use in controlled environments.

Cat. nr	Art. nr	Dimensions BxDxH (mm)	HE
Glass doors			
NSVE 64	53801	565x465x333	6
NSVE 104	53802	565x465x510	10
NSVE 154	53803	565x465x733	15
NSVE 214	53804	565x465x999	21
NSVE 106	53807	565x635x510	10
NSVE 156	53808	565x635x733	15
NSVE 216	53809	565x635x999	21
Metal doors			
NSVE 64-P	53811	565x465x333	6
NSVE 104-P	53812	565x465x510	10
NSVE 154-P	53813	565x465x733	15
NSVE 214-P	53814	565x465x999	21
NSVE 106-P	53817	565x635x510	10
NSVE 156-P	53818	565x635x733	15
NSVE 216-P	53819	565x635x999	21

