

# NSHV Wall-mounted enclosure

NSHV is a compact wall-mounted enclosure for 19-inch vertical installation with a height of 4 HU, resulting in a shallow enclosure depth of 220 mm.

The enclosure has two doors for optimal access and a generous assembly depth of 490 mm.



## Technical data

- Finish, textured Enoc System Beige.
- Protection degree IP 20.
- Maximum assembly depth 490 mm.



Type designation	Beige		Art.No. Metal door	Dimensions W x D x H (mm)	Weight (kg)	HU
	Art.No. Glass door	Version				
NSHV 626	53701	-P	53711	600x220x600	12	4

NSHV 626 has a glass door. If -P is added to the type designation (NSHV 626-P), the enclosure has a metal door.

**Enclosure**

A stable wall-mounted enclosure made completely of bent sheet steel.

**Door**

The enclosure has two doors. The side door is made of 1.25 mm sheet steel or a combination of 1.25 thick sheet steel and 3 mm thick glass. Door opening angle 110°. The front door is made of 1.25 mm sheet steel. Door opening angle 180°. Lock LS 35 in both doors, with standard lock cylinder for key C 101. Other keys are available as options.

**Side panels**

The side panels are made of 1.0 mm sheet steel, with holes for vertical mounting of accessories.

**Top**

The top has an adjustable cable gland with a foam rubber seal. It also has a ventilation grid that can be fitted with a fan (FT 01) or filter (LG 10K).

**Bottom**

Same configuration as top.

**19-inch**

The enclosure comes with a fixed 19-inch frame in sheet steel, 100 mm from inside of side door.

**Back**

The enclosure comes with a fixed integrated back panel.

**Wall mounting**

The back panel has keyholes in several directions for flexible wall mounting.

**Accessories**

Shelf (FH-NSHV) for mounting directly on back panel. See table on next page.

