

Fo1 IT Frame Beige

Thanks to Enoc System's stepless assembly system, you can put your equipment exactly where you want it in the Fo1. With the option of off-centre positioning, you can create plenty of space where you need it. A large space on both sides, or an extra large space on one side.

Fo1 is built with aluminium profiles and supports up to 1,500 kilos. The frame is assembled with nothing but screws, making it easy to assemble, dismantle and reassemble. The Fo1 can be adapted as your business grows and changes.

Enoc IT frames look so good that they are as suitable in an office as in a server room. The Fo1 is definitely no exception. Its rounded corners give it a sleek look. Concealed screws and aluminium profiles contribute to a streamlined appearance.



- Fo1 frames are available in heights of 20, 24, 29, 33, 38, 42 and 47 HU in combination with widths of 600 and 800 mm and depths of 600, 800, 1,000 and 1,200 mm.
- Screw-assembled frame with aluminium profiles and die-cast zinc corners. The frame has two integrated vertical screw pockets in each corner profile for universal mounting of accessories.
- Frame can be dismantled by means of screws.
- Finish: Enoc System textured beige.
- Maximum static load 1,500 kg, and divided on 4 19" profiles.
- Fo1-frame has no doors or side panels. Can be supplemented with doors and side panels from our range of accessories.
- Frame without top panels. Can be supplemented with top panels from our range of accessories.
- The base is open, but can be fitted with cover plate/base plate packages.
- The 19-inch profiles can be steplessly repositioned through the depth of the enclosure. The depth profiles have markings for precise positioning of the 19-inch profiles. The 19-inch profiles are numbered in height units. The whole 19-inch assembly can be moved right or left to an off-centre position. Frames with a depth of ≤ 800 mm have one pair of 19-inch profiles pre-installed at a depth of 100 mm from the front of the frame. Frames with a depth of $\geq 1,000$ mm have two pairs of 19-inch profiles. One pair is pre-installed at a depth of 100 mm from the front of the frame and the other pair is pre-installed 740 mm further in.
- 1 central earthing point M5 in corner upright.

Fo1 Beige						
Type designation	Art.No.	EAN-number	Width	Depth	Height	HU
Fo1 6610	55771	7330701085703	600	600	1000	20
Fo1 6810	55772	7330701085710	600	800	1000	20
Fo1 61010	55774	7330701085734	600	1000	1000	20
Fo1 8610	55776	7330701085758	800	600	1000	20
Fo1 8810	55777	7330701085765	800	800	1000	20
Fo1 81010	55779	7330701085789	800	1000	1000	20
Fo1 6612	55781	7330701085802	600	600	1200	24
Fo1 6812	55782	7330701085819	600	800	1200	24
Fo1 61012	55784	7330701085833	600	1000	1200	24
Fo1 8612	55786	7330701085857	800	600	1200	24
Fo1 8812	55787	7330701085864	800	800	1200	24
Fo1 81012	55789	7330701085888	800	1000	1200	24
Fo1 6614	55791	7330701085901	600	600	1400	29
Fo1 6814	55792	7330701085918	600	800	1400	29
Fo1 61014	55794	7330701085932	600	1000	1400	29
Fo1 8614	55796	7330701085956	800	600	1400	29
Fo1 8814	55797	7330701085963	800	800	1400	29
Fo1 81014	55799	7330701085987	800	1000	1400	29
Fo1 6616	55801	7330701086007	600	600	1600	33
Fo1 6816	55802	7330701086014	600	800	1600	33
Fo1 61016	55804	7330701086038	600	1000	1600	33
Fo1 8616	55806	7330701086052	800	600	1600	33
Fo1 8816	55807	7330701086069	800	800	1600	33
Fo1 81016	55809	7330701086083	800	1000	1600	33
Fo1 6618	55811	7330701086106	600	600	1800	38
Fo1 6818	55812	7330701086113	600	800	1800	38
Fo1 61018	55814	7330701086137	600	1000	1800	38
Fo1 8618	55816	7330701086151	800	600	1800	38
Fo1 8818	55817	7330701086168	800	800	1800	38
Fo1 81018	55819	7330701086182	800	1000	1800	38

Fo1 Beige						
Fo1 6620	55821	7330701086205	600	600	2000	42
Fo1 6820	55822	7330701086212	600	800	2000	42
Fo1 61020	55824	7330701086236	600	1000	2000	42
Fo1 61220	55825	7330701086243	600	1200	2000	42
Fo1 8620	55826	7330701086250	800	600	2000	42
Fo1 8820	55827	7330701086267	800	800	2000	42
Fo1 81020	55829	7330701086281	800	1000	2000	42
Fo1 81220	55830	7330701086298	800	1200	2000	42
Fo1 6622	55831	7330701086304	600	600	2200	47
Fo1 6822	55832	7330701086311	600	800	2200	47
Fo1 61022	55834	7330701086335	600	1000	2200	47
Fo1 61222	55835	7330701086342	600	1200	2200	47
Fo1 8622	55836	7330701086359	800	600	2200	47
Fo1 8822	55837	7330701086366	800	800	2200	47
Fo1 81022	55839	7330701086380	800	1000	2200	47
Fo1 81222	55840	7330701085397	800	1200	200	47