

W3 Wall cabinet

W3 is a series of wall-mounted enclosure with design for smaller network installation and passive network components. W3-series is available in heights 6, 9, 12, 15 and 21 HU and depths of 500 and 600 mm.



- Made of bent sheet steel.
- Surface treatment, textured Enoc System beige or black RAL 9005.
- Glass door is made of safety glass.
- Door opening angle 110°.
- Sheet steel sides, detachable.
- Top and bottom plates have knock-outs for cable glands. Supplied with edging strip for cable protection.
- Passive ventilation in top and bottom.
- 19" hole pattern in rear uprights for mounting accessories.
- One pair of 19-inch profiles (482.6 mm) pre-fitted 80 mm in from the enclosure front, can be repositioned at 25 mm intervals through depth of the enclosure.
- Extra pair of 19" profiles available as accessory.
- Keyholes for wall mounting.
- Open back, the back panel as accessory.
- Maximum static load 40 kg.
- Ingress protection class IP 20.

W3 Beige							
Type designation	Art.No.	EAN-number	Width	Depth	Height	Max. static load	HU
W3 6-5	57411	7330701103100	550	500	314	30 kg	6
W3 9-5	57412	7330701103117	550	500	448	30 kg	9
W3 12-5	57413	7330701103124	550	500	581	35 kg	12
W3 15-5	57414	7330701103131	550	500	714	35 kg	15
W3 21-5	57416	7330701103155	550	500	979	40 kg	21
W3 6-6	57421	7330701103209	550	600	314	30 kg	6
W3 9-6	57422	7330701103216	550	600	448	30 kg	9
W3 12-6	57423	7330701103223	550	600	581	35 kg	12
W3 15-6	57424	7330701103230	550	600	714	35 kg	15
W3 21-6	57426	7330701103254	550	600	979	40 kg	21

W3 Black							
Type designation	Art.No.	EAN-number	Width	Depth	Height	Max. static load	HU
W3 6-5-S	57441	7330701103407	550	500	314	30 kg	6
W3 9-5-S	57442	7330701103414	550	500	448	30 kg	9
W3 12-5-S	57443	7330701103421	550	500	581	35 kg	12
W3 15-5-S	57444	7330701103438	550	500	714	35 kg	15
W3 21-5-S	57446	7330701103452	550	500	979	40 kg	21
W3 6-6-S	57451	7330701103506	550	600	314	30 kg	6
W3 9-6-S	57452	7330701103513	550	600	448	30 kg	9
W3 12-6-S	57453	7330701103520	550	600	581	35 kg	12
W3 15-6-S	57454	7330701103537	550	600	714	35 kg	15
W3 21-6-S	57456	733001103551	550	600	979	40 kg	21