


## BS-250A FOUR POLE INSULATING SUPPORT

### CATALOG NUMBER

**BS-250A**



### CERTIFICATIONS



### FEATURES

Create custom four pole distribution blocks for an electrical distribution system

Mounts with screws

Protection screen can be fixed using spacers

Halogeenvrij

RoHS compliant

### PRODUCT ATTRIBUTES

Article Number: 551300

Material: Steel;Glass Fibre Reinforced Polyamide

Finish: Elektrolytisch gegalvaniseerd

Max Working Voltage, IEC (Ui): 630 VAC;630 VDC

Working Temperature: -40 to 130 °C

Typical Application Current Rating: 160 – 250 A

Complies With: IEC® 60439.1;IEC® 61439.1;IEC® 60695-2-11 (Glow Wire Test 960 °C)


Flammability Rating: UL® 94V-0

Busbar Width: 15 – 20 mm
Busbar Thickness: 5 mm
Depth: 45 mm
Height: 150 mm
A: 130 mm
Screw Diameter: M6
Unit Weight: 0.050 kg

ADDITIONAL PRODUCT DETAILS

Must be used with copper busbars.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

<b>Noord-Amerika</b> +1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support	<b>Europa</b> Netherlands: +31 800-0200135 France: +33 800 901 793	<b>Europa</b> Germany: 800 1890272 Other Countries: +31 13 5835404	<b>APAC</b> Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500
---	--	--	--