

## CATALOG NUMBER

**TDL-400A**



## CERTIFICATIONS



## FEATURES

Connect nVent ERIFLEX Flexibar, insulated braided conductor or cable with lug on line side

Tinned copper bars allows for copper or aluminum cable

Transparent protection covers

Easy and safe connections

Easily clips onto DIN rail or mounts to panel with screws

Solid bars provide reliability

Input separated from outputs

Supports wiring from both sides

Design allows for visual inspection of conductor and confirmation of connection

Large end terminals

High percentage of fill ratio

Wiring with or without terminal

RoHS compliant

Conforms to EN 45545 obtaining an HL3 classification for chapter R23 and HL2 classification for chapter R22

Halogeenvrij

## PRODUCT ATTRIBUTES

Article Number: 563995

Material: Copper;Thermoplastic

Finish: Vertind

Max Current Rating, IEC: 400 A

Max Current Rating, UL/CSA: 400 A

Short Term Withstand Current (I<sub>cw</sub>) 1s: 23 kA

Peak Short Circuit Current (I<sub>pk</sub>): 51 kA

Max Working Voltage, IEC (U<sub>i</sub>): 1,000 VAC;1,500 VDC

Max Working Voltage, UL (V<sub>in</sub>): 600 V

Line Side Number of Connections: 1

Line Side Compact Stranded Wire Size: 35 - 120 mm<sup>2</sup>

Line Side Conductor Width: 20 – 24 mm

Line Side Stranded Wire Size - Ferrule: 35 – 120 mm<sup>2</sup>

Line Side Wire Size: 1/0 – 250 kcmil

Load Side Number of Connections: 14

Load Side Compact Stranded Wire Size: (1) 10 - 50 mm<sup>2</sup>;(2) 10 - 35 mm<sup>2</sup>;(4) 6 - 25 mm<sup>2</sup>;(7) 2,5 - 16 mm<sup>2</sup>

Load Side Stranded Wire Size - Ferrule: (1) 10 - 35 mm<sup>2</sup>;(2) 10 – 25 mm<sup>2</sup>;(4) 6 - 16 mm<sup>2</sup>;(7) 2,5 - 10 mm<sup>2</sup>

Load Side Wire Size: (1) #6 – 1/0;(2) #8 - #1;(4) #10 - #3;(7) #10 - #5

Depth: 121 mm

Height: 156 mm

Width: 224 mm

Unit Weight: 1.690 kg

Enclosure Rating: IP 10

Flammability Rating: UL® 94V-0





Complies With: IEC® 60947-7-1

## ADDITIONAL PRODUCT DETAILS

Line side and load side number of connections are per pole.

Design Guideline for Distribution Blocks, Power Blocks and Power Terminals										
Derating according to Ambient* Temperature (°C) to maintain working temperature of 85°C										
Ambient Temperature (°C)	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°
Derating Coefficient (d)	1	1	1	0.94	0.88	0.82	0.75	0.67	0.58	0.47
*environment around the terminal blocks inside the enclosure										

## DIAGRAMS



## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

### Noord-Amerika

+1.800.753.9221  
Option 1 – Customer Care  
Option 2 – Technical Support

### Europa

Netherlands:  
+31 800-0200135  
France:  
+33 800 901 793

### Europa

Germany:  
800 1890272  
Other Countries:  
+31 13 5835404

### APAC

Shanghai:  
+ 86 21 2412 1618/19  
Sydney:  
+61 2 9751 8500



Our powerful portfolio of brands:  
**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF**  
**TRACER**