

## BALKKLEM, GETAPT M6, 16 MM MAX. FLENS

### CATALOG NUMBER

**EBC**



### CERTIFICATIONS



### FEATURES

Eenvoudige montage op balkflenzen

One 10.5mm go-through hole allows the use of M6, M8 or M10 threaded rod, to attach any static load till 450N

Met drie M6-draadgaten om opbouwdozen rechtstreeks aan de zijkant of onderkant van de balk te bevestigen

### PRODUCT ATTRIBUTES

Article Number: 170380

Material: Veerstaal

Finish: nVent CADDY gepantserd

Rod Size: M6

Hole Size: 10.50 mm

Flange Thickness: 16 mm Max


Torque: 3 N-m

Static Load: 450 N

ADDITIONAL PRODUCT DETAILS

Stelschroef moeten worden vastgezet met aanhaalmoment op de schuine kant van het I-profiel.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika

+1.800.753.9221  
Option 1 – Customer Care  
Option 2 – Technical Support

Europa

Netherlands:  
+31 800-0200135  
France:  
+33 800 901 793

Europa

Germany:  
800 1890272  
Other Countries:  
+31 13 5835404

APAC

Shanghai:  
+ 86 21 2412 1618/19  
Sydney:  
+61 2 9751 8500



Our powerful portfolio of brands:  
**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF**  
**TRACER**