

KOPEREN AARDINGSPEN, SCHROEFDR., 5/8" DIA, 5' (1.5M), 10 MIL, 4.2 LB (1.9 KG)

CATALOG NUMBER

635850



FEATURES

Koudgewalste schroefdraad met continue, ongebroken vezels is veilig voor de kopercoating en is sterker dan gesneden schroefdraad

99.9% pure electrolytic copper coating

Pennen hebben een stalen kern met een hoog koolstofgehalte die zorgen voor een superieure stijfheid bij het indrijven

Koperen coating zal niet breken of scheuren wanneer de pen tijdens het indrijven wordt gebogen

Minimum copper coating of 10 mils on rods listed to UL® 467

nVent ERICO name, length, diameter and part number is roll-stamped within 12" (304,8 mm) of chamfered end

UL-logo en eventueel het controlenummer zijn in elke stang gestanst, voor gemakkelijke identificatie na de plaatsing

PRODUCT ATTRIBUTES

Material: Kopergebonden staal

Tensile Strength: 552 MPa Min

Thread Location: Puntige en afgeschuinde uiteinden

Ground Rod Diameter, Nominal: 5/8"

Ground Rod Diameter, Actual: 14.2 mm

Thread Size: 5/8" UNC

Length: 1.500 m

Plating Thickness: 254 µm


Unit Weight: 1.900 kg

ADDITIONAL PRODUCT DETAILS

For rods to be listed to UL® 467, they must be at least 8' (2.44 m) in length.

IEC® EN 62561-2 supercedes EN 50164-2.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

⚠ WARNING: This product can expose you to chemicals including nickel, which is known to the State of California to cause cancer and birth defects or other reproductive harm.- For more information go to-www.P65Warnings.ca.gov.

Noord-Amerika +1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support	Europa Netherlands: +31 800-0200135 France: +33 800 901 793	Europa Germany: 800 1890272 Other Countries: +31 13 5835404	APAC Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500
---	--	--	--