

Article-No: 9600212

High Bay Luminaires

High bay luminaires COMO BL 150 ø380mm 1x150W wide100° PC




LED high bay in compact circular design with integrated ballast unit, optimized covering lens made of polycarbonate for glare limitation, housing made of aluminium alloy, white powder-coating, short ageing-resistant silicone seals, mounting with eyelet suspension, wall and ceiling mounting possible with extra accessory, without through-wiring.

EAN

4018098304555

Statistical product
number

94054099



LAMP

Product type	LED
Number of lamps /LED-rows	1
Color temperature K	4.000
Color rendering index	>80
Amount LED	288
Color tolerance (initial MacAdam)	5

POWER

Luminous flux lm	20500
Systempower W	150
Efficacy lm/W	137

LIGHT ENGINEERING

Light distribution	wide beam
Light distribution angle in °	100
Unified Glare Rating UGR 4H 8H C0 C90	27.4 / 27.6

TECHNICAL DATA

Nominal voltage	220-240V 50/60 Hz
Protection class SK	I
Ballast	LED-converter on/off
Through-wiring mm²	without
Glow wire test	650 °C - 5 sec.
D-rating	yes
Certification mark	ENEC
Type of voltage	AC
Circuit breaker B10A	2
Circuit breaker B16A	4
Circuit breaker C10A	4
Circuit breaker C16A	7

CAPACITY

IK-Impact resistance	08
Warranty (years)	3
L80/B10 Lebensdauer bei 25°C	100000
L70/B50 Life expectancy at 25°C	100000
Unprotected outdoor areas	not suitable
max. lowest temperature in °C	-40
max. highest temperature in °C	50
Ingress protection class	65
Agricultural use	unsuitable

DIMENSIONS AND WEIGHT

Length mm	380
Width mm	380
Height mm	123
Outside diameter in mm	380
Weight netto in kg	3.9

PACKAGING

Length m VPE	0.44
Width VPE in m	0.44
Height VPE in m	0.17
Weight incl. packaging kg	4.5

ASSEMBLY AND MAINTENANCE

Standard installation	Pendulum
Optional installation	Ceiling, Wall
exchangeable LED board	not possible

MATERIAL

Case color	white RAL9003
Renewable resources possible	no
Housing material	Aluminium
Cover material	PC

The right of error and later technical developments is reserved.

State: 14.05.2020