



WEVER & DUCRÉ
LIGHTING

BOX 2.0 PAR16

146220B0

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Surface

Jet Black

IP20

Interior

915^a to 925^b lm

RAL 9005^c

LED

Lamp 2 x PAR16

PAR16

Socket GU10

max. 12 W

CRI $\geq$ 80

OPTICAL

Beam angle 47°

PHYSICAL

Length 188 mm

Width 100 mm

Height 100 mm

1.13 kg

ELECTRICAL

100 - 240 V

Total connected power 13.2^b to 13.3^a

W

Class 1

Safety distance 0.3 m


^a LED 3000K CRI 80 white

^b LED 2700K CRI 80 white


^c Color may deviate slightly due to production conditions.



Rectangular ceiling surface mounted downlight made from die-cast aluminium; surface Jet Black; powder coated; matt texture; RAL 9005; optional double inner reflector and single inner cover available; lamp socket GU10; lamp type PAR16; 2x max. 12W; 100 - 240 V; degree of protection IP20; PC1; UGR 19; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° 3000 cd/m²; lamp not included;



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

BOX 2.0 PAR16

146220B0

CONE DIAGRAM

LED 2700K CRI ≥ 80 White

h (m)	EO° (lx)	ø (m)
1	1290	0.88
2	320	1.75
3	140	2.63
4	80	3.50
5	50	4.38

INNER REFLECTOR

Double Inner Reflector

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
BOX 2.0 max. 10W	Black	181-93-50	9 1 1 2 5 1 B 1
BOX 2.0 max. 10W	Gold	181-93-50	9 1 1 2 5 1 G 1
BOX 2.0 max. 10W	White	181-93-50	9 1 1 2 5 1 W 1

INNER COVER

Single Inner Cover

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
BOX max. 10W	Black	62-62-49	9 1 1 0 1 1 B 1
BOX max. 10W	Gold	62-62-49	9 1 1 0 1 1 G 1
BOX max. 10W	White	62-62-49	9 1 1 0 1 1 W 1

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	ø50-58	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	ø50-58	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	ø50-58	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	ø50-58	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	ø50-52	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	ø50-52	9 0 5 2 2 7 S 4