



WEVER & DUCRÉ
LIGHTING

DEEP 1.0 PAR16

112120W0C

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Recessed

Signal White

IP20

Interior

495 lm

RAL 9003 ^a

LED

Lamp PAR16

PAR16

Socket GU10

max. 12 W

CRI 90

OPTICAL

Wide Flood

Beam angle 48°

PHYSICAL

Diameter 84 mm

Height 102 mm

0.29 kg

blade springs

ELECTRICAL

100 - 240 V

LED Inset 6.5 W

Class 2

Safety distance 0.3 m


CUTOUT

Diameter 76-79 mm


Min. ceiling thickness 10 mm

Recessed depth 105 mm

^a Color may deviate slightly due to production conditions.



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

DEEP 1.0 PAR16

112120W0C

CONE DIAGRAM

wide flood 48°

h (m)	EO° (lx)	ø (m)
1	700	0.89
2	175	1.78
3	78	2.67
4	44	3.56
5	28	4.45

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	ø50 · 58	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	ø50 · 58	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	ø50 · 58	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	ø50 · 58	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	ø50 · 52	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	ø50 · 52	9 0 5 2 2 7 S 4