



WEVER & DUCRÉ
LIGHTING

MATCH on STREX 3.0

179265M5

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Track Suspended

Champagne

IP20

Interior

520 lm

LED

3000 K

OPTICAL

Beam angle 33°

ELECTRICAL

DALI dim

48 V

Total connected power 8.0 W

LED Inset 8.0 W

Class 3

Safety distance 0.3 m

PHYSICAL

Cable 1200mm


Diameter 26 mm

Height 300 mm


0.2 kg

171 (adapter)mm

48V System



Suspended luminaire for 48V tracks made from aluminium; track adapter with height adjustable cable system; surface Champagne; powder coated; matt texture; polycarbonate track adapter and cable in Signal Black; with COB (Chip on Board) technology for maximum efficiency; DALI dim; light colour 3000 K; 48 V; degree of protection IP20; PC3; light source replaceable by an authorized professional;





WEVER & DUCRÉ
LIGHTING

MATCH on STREX 3.0

179265M5

RECESSED

End Cap

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system recessed	White	37·10·27	9 0 0 1 4 1 4 9
STREX system recessed	Black	37·10·27	9 0 0 1 4 1 5 0

Track Profile 1m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system recessed	White	1000·37·33	9 0 0 1 4 1 8 7
STREX system custom cut recessed	White	200-999·37·33	9 0 0 1 4 1 8 7 C C
STREX system recessed	Black	1000·37·33	9 0 0 1 4 1 8 8
STREX system custom cut recessed	Black	200-999·37·33	9 0 0 1 4 1 8 8 C C

Track Profile 2m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system recessed	White	2000·37·33	9 0 0 1 4 1 8 9
STREX system custom cut recessed	White	1001-1999·37·33	9 0 0 1 4 1 8 9 C C
STREX system recessed	Black	2000·37·33	9 0 0 1 4 1 9 0
STREX system custom cut recessed	Black	1001-1999·37·33	9 0 0 1 4 1 9 0 C C

Track Profile 3m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system recessed	White	3000·37·33	9 0 0 1 4 1 9 1
STREX system custom cut recessed	White	2001-2999·37·33	9 0 0 1 4 1 9 1 C C
STREX system recessed	Black	3000·37·33	9 0 0 1 4 1 9 2
STREX system custom cut recessed	Black	2001-2999·37·33	9 0 0 1 4 1 9 2 C C

Mounting Bracket

TYPE	ORDERCODE
STREX system recessed	9 0 0 1 4 1 9 3

L-Connector non-electrical

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system recessed	White	105·105·19	9 0 0 1 4 2 5 6
STREX system recessed	Black	105·105·19	9 0 0 1 4 2 5 7

SURFACE

End Cap

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface/suspended	White	26·2.5·29	9 0 0 1 4 1 4 7
STREX system surface/suspended	Black	26·2.5·29	9 0 0 1 4 1 4 8
STREX system surface/suspended	Champagne	26·2.5·29	9 0 0 1 4 3 4 7
STREX system surface/suspended	Bronze	26·2.5·29	9 0 0 1 4 3 4 8



WEVER & DUCRÉ
LIGHTING

MATCH on STREX 3.0

179265M5

Track Profile 1m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface/suspended	White	1000-26-29	9 0 0 1 4 1 8 1
STREX system custom cut surface/suspended	White	200-999-26-29	9 0 0 1 4 1 8 1 C C
STREX system surface/suspended	Black	1000-26-29	9 0 0 1 4 1 8 2
STREX system custom cut surface/suspended	Black	200-999-26-29	9 0 0 1 4 1 8 2 C C

Track Profile 2m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface/suspended	White	2000-26-29	9 0 0 1 4 1 8 3
STREX system custom cut surface/suspended	White	1001-1999-26-29	9 0 0 1 4 1 8 3 C C
STREX system surface/suspended	Black	2000-26-29	9 0 0 1 4 1 8 4
STREX system custom cut surface/suspended	Black	1001-1999-26-29	9 0 0 1 4 1 8 4 C C
STREX system surface/suspended	Champagne	2000-26-29	9 0 0 1 4 3 8 3
STREX system custom cut surface/suspended	Champagne	1001-1999-26-29	9 0 0 1 4 3 8 3 C C
STREX system surface/suspended	Bronze	2000-26-29	9 0 0 1 4 3 8 4
STREX system custom cut surface/suspended	Bronze	1001-1999-26-29	9 0 0 1 4 3 8 4 C C

Track Profile 3m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface/suspended	White	3000-26-29	9 0 0 1 4 1 8 5
STREX system custom cut surface/suspended	White	2001-2999-26-29	9 0 0 1 4 1 8 5 C C
STREX system surface/suspended	Black	3000-26-29	9 0 0 1 4 1 8 6
STREX system custom cut surface/suspended	Black	2001-2999-26-29	9 0 0 1 4 1 8 6 C C
STREX system surface/suspended	Champagne	3000-26-29	9 0 0 1 4 3 8 5
STREX system custom cut surface/suspended	Champagne	2001-2999-26-29	9 0 0 1 4 3 8 5 C C
STREX system surface/suspended	Bronze	3000-26-29	9 0 0 1 4 3 8 6
STREX system custom cut surface/suspended	Bronze	2001-2999-26-29	9 0 0 1 4 3 8 6 C C

L-Connector non-electrical

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface	White	105-105-19	9 0 0 1 4 2 5 8
STREX system surface	Black	105-105-19	9 0 0 1 4 2 5 9

SUSPENDED

Track Profile 2m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system suspended indirect light	Black	2000-26-29	9 0 0 1 4 0 B 5
STREX system custom cut suspended indirect light	Black	1000-1999-26-29	9 0 0 1 4 0 B 5 C C
STREX system suspended indirect light	White	2000-26-29	9 0 0 1 4 0 W 5
STREX system custom cut suspended indirect light	White	1000-1999-26-29	9 0 0 1 4 0 W 5 C C

[179265M5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com

March 22, 2023



WEVER & DUCRÉ
LIGHTING

MATCH on STREX 3.0

179265M5

Suspension Set

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system 1.5m suspended	Stainless Steel	80·23·1500	9 0 0 1 4 1 6 0
STREX system 3.0m suspended	Stainless Steel	80·23·3000	9 0 0 1 4 1 6 1
STREX system 1.5m suspended	Black	80·23·1500	9 0 0 1 4 2 7 4
STREX system 3.0m suspended	Black	80·23·3000	9 0 0 1 4 2 7 5

Track Profile 3m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system suspended indirect light	Black	3000·26·29	9 0 0 1 4 1 B 5
STREX system custom cut suspended indirect light	Black	2001·2999·26·29	9 0 0 1 4 1 B 5 C C
STREX system suspended indirect light	White	3000·26·29	9 0 0 1 4 1 W 5
STREX system custom cut suspended indirect light	White	2001·2999·26·29	9 0 0 1 4 1 W 5 C C

COVER

Blank Cover 1m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system	Black	1000·18·3	9 1 1 0 0 1 B 0
STREX system	White	1000·18·3	9 1 1 0 0 1 W 0

Blank Cover 2m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system	Black	2000·18·3	9 1 1 0 0 2 B 0
STREX system	White	2000·18·3	9 1 1 0 0 2 W 0

Blank Cover 3m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system	Black	3000·18·3	9 1 1 0 0 3 B 0
STREX system	White	3000·18·3	9 1 1 0 0 3 W 0

ELECTRICAL

In Track Driver 100W

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface	Black	438·16·18	9 0 0 1 4 1 4 3
STREX system surface	White	438·16·18	9 0 0 1 4 1 4 4
STREX system suspended	White	3000	9 0 0 1 4 1 5 7
STREX system suspended	Black	3000	9 0 0 1 4 1 7 4
STREX system surface	Black	468·26·29	9 0 0 1 4 1 7 6
STREX system surface	White	468·26·29	9 0 0 1 4 1 7 8
STREX system surface	Bronze + Black	468·26·29	9 0 0 1 4 3 7 6
STREX system surface	Champagne + Black	468·26·29	9 0 0 1 4 3 7 8



WEVER & DUCRÉ
LIGHTING

MATCH on STREX 3.0

179265M5

In Track Driver 250W

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface	Black	408-16-18	9 0 0 1 4 1 4 5
STREX system surface	White	408-16-18	9 0 0 1 4 1 4 6
STREX system suspended	White	3000	9 0 0 1 4 1 5 8
STREX system suspended	Black	3000	9 0 0 1 4 1 7 5
STREX system surface	Black	438-26-29	9 0 0 1 4 1 7 7
STREX system surface	White	438-26-29	9 0 0 1 4 1 7 9
STREX system surface	Bronze + Black	438-26-29	9 0 0 1 4 3 7 7
STREX system surface	Champagne + Black	438-26-29	9 0 0 1 4 3 7 9

Power Feed

TYPE	COLOUR	L · H (MM)	ORDERCODE
STREX system	White	112-18	9 0 0 1 4 1 5 3
STREX system	Black	112-18	9 0 0 1 4 1 5 4

Wireless Casambi Control

TYPE	COLOUR	L · H (MM)	ORDERCODE
STREX system	White	143-58	9 0 0 1 4 1 5 5
STREX system	Black	143-58	9 0 0 1 4 1 5 6

Power Supply 100W

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface	White	439-26-44	9 0 0 1 4 1 6 6
STREX system surface	Black	439-26-44	9 0 0 1 4 1 6 7
STREX system suspended	White	439-26-44	9 0 0 1 4 1 6 8
STREX system suspended	Black	439-26-44	9 0 0 1 4 1 6 9
STREX system suspended	White	439-26-44	9 0 0 1 4 2 6 0
STREX system suspended	Black	439-26-44	9 0 0 1 4 2 6 1

Power Supply 150W

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface	White	439-26-44	9 0 0 1 4 1 7 0
STREX system surface	Black	439-26-44	9 0 0 1 4 1 7 1
STREX system suspended	White	439-26-44	9 0 0 1 4 1 7 2
STREX system suspended	Black	439-26-44	9 0 0 1 4 1 7 3
STREX system suspended	White	439-26-44	9 0 0 1 4 2 6 2
STREX system suspended	Black	439-26-44	9 0 0 1 4 2 6 3

Connector

TYPE	COLOUR	L · H (MM)	ORDERCODE
STREX system	White	105-18	9 0 0 1 4 1 9 6
STREX system	Black	105-18	9 0 0 1 4 1 9 7

L-Connector

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface/suspended	White	105-105-18	9 0 0 1 4 1 9 8
STREX system surface/suspended	Black	105-105-18	9 0 0 1 4 1 9 9
STREX system recessed	White	105-105-18	9 0 0 1 4 2 5 1
STREX system recessed	Black	105-105-18	9 0 0 1 4 2 5 2
STREX system surface/suspended	Champagne + Black	105-105-18	9 0 0 1 4 3 9 8
STREX system surface/suspended	Bronze + Black	105-105-18	9 0 0 1 4 3 9 9

[179265M5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com

March 22, 2023



WEVER & DUCRÉ
LIGHTING

MATCH on STREX 3.0

179265M5

T-Connector

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface	White	275 · 146 · 18	9 0 0 1 4 2 9 2
STREX system surface	Black	275 · 146 · 18	9 0 0 1 4 2 9 3

X-Connector

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface	Black	275 · 275 · 18	9 0 0 1 4 2 9 4
STREX system surface	White	275 · 275 · 18	9 0 0 1 4 2 9 5

DALI Selv Device

TYPE	L · W · H (MM)	ORDERCODE
STREX system	213 · 37 · 25	9 0 0 1 9 1 9 3



Driver

TYPE	L · W · H (MM)	ORDERCODE
STREX system 100W	350 · 30 · 18	9 0 2 1 8 9 0 1
STREX system 150W	350 · 30 · 18	9 0 2 1 8 9 0 2
STREX system 250W	400 · 40 · 22	9 0 2 1 8 9 0 3