



Verzinkte houtdraadbouten

- Verzinkte houtdraadbouten met zeskantkop
- Normering:** DIN 571/4.6

Bestelnr.	Ø mm	Lengte mm	Aantal
25.14.21.94	5	25	200
25.14.22.95	5	30	200
25.14.23.96	5	40	200
25.14.24.00	5	50	200
25.14.26.02	6	25	200
25.14.27.03	6	30	200
25.14.28.04	6	35	200
25.14.29.05	6	40	200
25.14.30.06	6	45	200
25.14.31.07	6	50	200
25.14.32.08	6	60	200
25.14.33.09	6	70	200
25.14.34.10	6	80	200
25.14.35.11	6	90	200
25.14.25.01	6	100	200
25.14.36.12	7	40	100
25.14.37.13	7	50	100
25.14.38.14	7	60	100
25.14.39.15	7	70	100
25.14.02.75	7	80	100
25.14.00.73*	7	100	100
25.14.01.74	7	120	100
25.14.45.21	8	30	200
25.14.46.22	8	40	200
25.14.47.23	8	45	200
25.14.48.24	8	50	200
25.14.49.25	8	60	100
25.14.50.26	8	70	100
25.14.51.27	8	80	100
25.14.52.28	8	90	100
25.14.40.16	8	100	100
25.14.41.17	8	120	100
25.14.42.18	8	140	50
25.14.43.19	8	150	50
25.14.44.20	8	160	50
25.14.10.83	10	40	100
25.14.11.84	10	50	100
25.14.12.85	10	60	100
25.14.13.86	10	70	100
25.14.14.87	10	80	50
08.58.40.92	10	90	50
25.14.03.76	10	100	50
25.14.04.77	10	120	50
25.14.05.78	10	140	50
25.14.06.79	10	160	50
25.14.07.80	10	180	50
25.14.08.81	10	200	50
25.14.09.82	10	240	25
25.14.19.92	12	60	100
25.14.20.93	12	80	50
25.14.15.88	12	100	50
25.14.16.89	12	120	25
25.14.17.90	12	140	25
25.14.18.91	12	160	25

* Geel verzinkt