

Products

Products Overview

Product Search

Evaluate

- Advertisements
- PDF-Reduce Insta ..
- PDF-TX6 10Gig UT ..
- Brochures
- PDF-TX6A 10Gig S ..
- FAQ's
- Performance Data
- PDF-Intertek 3 C ..
- PDF-Delta STP 4 ..
- Press Releases
- 10GIG Shield ..
- Selection Guides
- PDF-TX6A 10Gig S ..

Design a Solution

- Catalog Cut Sheet
- PDF-CJS6X88TGY P
- Part Drawings
- DXF-Mini-Com TX6 ..
- DWG-Mini-Com TX6 ..
- PDF-Mini-Com TX6 ..
- Specification Sheets
- PDF-TX6A 10Gig S ..
- PDF-Mini-Com TX6 ..

How to Buy

- Bill of Material
- Custom Order Forms
- Favorite Products List
- Locate Distributor

Install & Maintain

- Installation Instructions
- PDF-Mini-Com TX6 ..

Home > Products Overview > Product Search >

Current refinements (click to remove) Search Tips 

Part Number > CJS6X88TGY

Your search criteria matched only one product, shown below

CJS6X88TGY



- Exceed requirements of ANSI/TIA-568-C.2 Category 6A, IEEE 802.3an-2006, and ISO 11801 Class EA channel standards
- Exceed requirements of ANSI/TIA-568-C.2 Category 6A and IEC 61156-5 Category 6A component standards
- Meet requirements of IEEE 802.3af and IEEE 802.3at for PoE applications
- Each jack is 100% tested to ensure NEXT and RL performance and is individually serialized for traceability
- Utilize patent-pending enhanced Giga-TX™ Technology for jack terminations which optimizes performance by maintaining cable pair geometry and eliminating conductor untwist
- Fully grounded and bonded to patch panel when installed in Panduit All Metal Modular Patch Panel
- Contacts plated with 50 microinches of gold for superior performance
- No punchdown tool required; termination tool (EGJT) ensures conductors are fully terminated by utilizing a smooth forward motion without impact on critical internal components for maximum

reliability

- Optional termination tool (TGJT) reduces termination time by 25%, ideal for high volume installations
- Can be re-terminated a minimum of twenty times
- Blue termination cap designates 10Gig™ Category 6A performance and provides positive strain relief; helps control cable bend radius and securely retains wires
- Terminate 4-pair, 22 – 26 AWG, 100 ohm, solid or stranded shielded twisted pair cable
- Universal termination cap is color-coded for T568A and T568B wiring schemes
- Integrated strain relief with wire cap provides 360° conductive path for grounding
- .187" grounding tab provides conductive patch for grounding individual jacks
- Accept 6 and 8-position modular plugs without damage
- Can be clearly identified with optional labels and icons
- Compatible with Mini-Com® Modular Patch Panels, Faceplates, and Surface Mount Boxes
- Optional RJ45 Blockout device blocks out unauthorized access to jack modules and potentially harmful foreign objects, saving time and money associated with data security breaches, network downtime, repair and hardware replacement
- Optional Dust cap keeps out dust and debris while not in use
- Optional RJ45 Lock-in device blocks unauthorized removal of cable, IP phone, other networking equipment or critical connection

■ Part Number	CJS6X88TGY
■ RoHS Compliancy Status	Compliant
■ Note	CJS6X88TGY replaces CJS6X88TG
■ Part Description	Category 6A, RJ45, 10 Gb/s, 8-position, 8-wire universal shielded black module with integral shield.
■ Product Type	Shielded Jack Module
■ Material	Module housing - ABS Shield - Tin plated Phosphor Bronze Wire Cap - Plastic
■ Color	Black
■ Depth (In.)	1.50
■ Depth (mm)	38.1
■ Height (In.)	0.73
■ Height (mm)	18.6
■ Width (In.)	0.62
■ Width (mm)	15.8
■ CE Compliant	No
■ No. of Module Spaces	1
■ Performance Level	Category 6A/Class EA
■ Pricing Description	Mini-Com Module, Cat 6A, Shielded, 8 pos 8 wire, TG Style
■ Wiring Scheme	T568A/T568B
■ Min. Order UOM	PC
■ Min. Order Qty.	1
■ BOM Qty. (# of Pkgs.)	0
■ Add to Favorite Product List	☐

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

